



Product Data

Economy Anti Slip Floor Paint

Description:

Hard wearing polyurethane one pack paint designed to seal and colour concrete floors. Provides anti-slip properties for pedestrian traffic areas. Petrol and oil resistant, this product is ideal for general walkways, factory and garage floors. Excellent durability.

Area of use:

Interior

Substrates:

Concrete floors

Packing:

5 Litre and 20 Litre

Physical Constants:

Colours: Red, green, grey, black and blue

Finish: Semi gloss

Volume solids: 50%

Theoretical spreading rate: 15 sq. metres per litre

Actual Spreading rate: Approx 8-10 sq. metres per litre

Flash point: 38°C

Specific gravity: 1.4

Dry to touch: 2 - 4 hours (20°C)

Overcoating time: 16 hours

Intercoat time: 16 hours

The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. **The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method: Brush/roller Conventional spray Airless spray

Thinner: White Spirit

Cleaning of tools: White Spirit

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

Preparation: Bare concrete should be primed with the floor paint diluted by 10%

See MSDS for further information. For additional guidance please contact New Venture Product Ltd.