



Suppliers, Importers & Exporters LEISURE & INDUSTRIAL NETTING, TWINE & ROPE

Pelham industrial Estate, Manby Road, Immingham, DN40 2SE, UK

Tel: (01469) 575804

e-mail: netting@renco.co.uk

www.renco.co.uk

PRODUCT SPECIFICATION

PRODUCT	50MM BRAIDED POLYETHYLENE FLAME RETARDENT NETTING
RAW MATERIAL	POLETHYLENE HIGH DENSITY
COLOURS	BLACK
COMPOSITION	16 X 4 = 64 MONOFILAMENTS PE
CORE	NO CORE
EN ISO 11925-2 – EN 13501 - 1	CLASS 1
DIAMETER MONOFILAMENT PE	0.32MM = 600 DTEX
DIA.APPROX TWINE	3.6MM
RUNNAGE TWINE	260M/KG
BREAKING STRENGTH TWINE	94KG
ELONGATION AT BREAK	28%
HOT AIR 160° SHRINKAGE	15%
DENSITY	0.95GR/CM3 (FLOAT)
KNOT TO KNOT NETTING	57.5MM (115MM FULL MESH)
KNOT STRENGTH APPROX	71KG
WEIGHT SQUARE MESH	200GR
PRESENTATION	TERMOFIXED

