

The low level access solution that offers flexibility when working at 3m and below.



DELTADECK

The Deltadeck 250 is supplied as a complete folding unit with no loose components. It provides a 1,100mm X 600mm working area, a 3m Maximum Working Reach Height and a 200 Kg Safe Working Load. The Deltadeck 250 is manufactured under a BS ISO 9001 approved Quality System and meets the stringent load safety factor requirements of BS EN 1004.



EFFORTLESS ACCESS

- One person operation
- One complete unit (no pins, clips or components to lose, damage or forget about when assembling)
- Simple to assemble and dismantle
- Easy transportation and storage (can even be transported by car)
- Compact dimensions allow the Deltadeck to be moved from room to room while still assembled
- Can accommodate two people
- Weight 26.5 Kg
- Folded transport dimensions - 1,120mm x 760mm x 310mm

SAFE ACCESS

- Multiple platform heights (450mm, 530mm, 600mm, 730mm & 870mm)
- Fully guardrailed to ensure user safety at all times, at all heights
- Maximum working height of 3.0m
- Safe working load of 200kg
- Access and egress from either end of the platform



Toptower Ltd
Access House
Bromsgrove Road
Halesowen
West Midlands
Tel: 0121 585 5858
Fax: 0121 585 7989
Email: sales@toptower.co.uk
Web: www.toptower.co.uk