

RonaGrip Instant Safety Sheet

Pre-formed GRP slip resistant safety sheet



FEATURES

- highly slip resistant
- easy to apply
- can be trafficked instantly
- hard wearing and durable
- installed over virtually any substrate
- choice of size and colour
- corrosion resistant

Description

RonaGrip Instant Safety Sheet is a high quality composite of glass woven matting impregnated with polyester resin. The energy absorption and flexibility of the product, ensures its long life, even in the busiest of environments.

A compound of a special formula of grit is added in the final layer of laminate providing an excellent slip resistant and hard wearing surface.

RonaGrip Instant Safety Sheet is resistant to a wide range of chemicals and are perfectly suited for use even in the harshest of environments. Chemical resistance guides are available upon request.

The versatility of RonaGrip Instant Safety Sheet allows it to be applied to almost any surface such as concrete, steel or wood. The fact that it is supplied as a finished product means that it can be walked on straight away thus keeping disruption to a minimum.

Uses

- DDA and Building Regulations compliant
- Can be used on ramps or flat surfaces
- Internal and external application
- Suitable for industrial, commercial, retail and domestic use

Instructions for Use

Preparation

Prepare the surface and ensure that it is clean and free of any loose or friable material that can effect the adhesion.

Adhesive

Apply the RonaGrip Instant Adhesive MP10 onto the back of the sheet and onto the surface receiving the sheet.

RonaGrip Instant Safety Sheet

Pre-formed GRP slip resistant safety sheet

Instructions for Use (continued)

Installation

Carefully place the sheet onto the adhesive. Once in place, drill holes 15mm in from all edges at no more than 300mm apart from the centres. Depending on the width of the panels it may be necessary to provide fixing points at 600mm centres down the middle of the panels. As substrates vary considerably, additional fixings may be required to fix the panels down. If fixing down two pieces of flat sheet that is constrained by sides (i.e. a ramp with a wall on either side) a 5mm expansion gap should be considered between the two or more sheets. This gap can be filled with a standard high modulus mastic.

Packaging

Standard panel size is 2440mm x 1200mm x 4mm thick. A free cutting service is available to meet project requirements. The standard stock colours are black, yellow and stone. However, subject to minimum order quantities and extended delivery periods, any BS or RAL colour is available.

Slip Resistance

Using the pendulum test method, RonaGrip Instant Safety Sheet achieved a Slip Resistance Value of 105 in the dry (Extremely low risk) and 67 in the wet (extremely low risk).

Health and Safety

Non-hazardous. Protective clothing such as goggles, overalls and gloves is recommended to prevent any effect from prolonged skin contact, inhalation or ingestion of RonaGrip Instant Adhesive MP10. Refer to Health and Safety Data Sheet.

Site Attendance

When on site Ronacrete representatives are able, if asked, to give a general indication of the correct method of installing a Ronacrete product. It is important to bear in mind that Ronacrete Ltd is a manufacturer and not an application contractor and it is therefore the responsibility of the contractor and his employer to ensure he is aware of and implements the correct practices and procedures to ensure the correct installation of the product and that liability for its correct installation lies with the contractor and not with Ronacrete Ltd.

The information detailed in this leaflet is liable to modification from time to time in the light of experience and of normal product application, and before using, customers are advised to check with Ronacrete Ltd, quoting the reference number, that they possess the latest issue. Any person or company using the product without first making further enquiries as to the suitability of the product for the intended use does so at his own risk, and Ronacrete Ltd can accept no responsibility for the performance of the product, or for any loss or damage arising out of such use.