



Intermec

Product Profile

- Versatile, the EasyCoder E4 enhances productivity and is easy to use.
- Designed with the operator in mind: supplied with Connect & Print™ features, like LabelShop® START™ software, label and ribbon rolls, Windows™ driver, and parallel computer connection cable.
- Robust Feature Set allows the user to address multiple applications.
- Compact, the EasyCoder E4 will fit virtually anywhere.
- Easy to load ribbons and labels, reduces down time and increases productivity.
- RS-232 and Centronics® Parallel Connections are standard features.
- Peel off function with Label-Taken sensor for internal rewind of backing paper is also standard.
- The EasyCoder E4 printer is also available in a LinerLess version.



E A S Y C O D E R ® E 4 P R I N T E R

The EasyCoder E4 provides a reliable thermal transfer and direct thermal printing solution in numerous environments. Compact in design, the EasyCoder E4 printer is ideal where space is limited and performance is required.

The EasyCoder E4 is packed with features that would normally be considered options with other printers in the same class. For quick and easy printing, the printer is supplied with Intermec's Connect and Print® features: LabelShop® START Label Design & Print software, InterDriver™ with ActiveX® controls Windows™ driver, parallel computer connection cable, and sample roll of labels and ribbon.

The EasyCoder E4 comes standard with 1MB of FLASH memory, two PC card slots, internal rewinder, Label Taken Sensor, plus RS-232 and Centronics® Parallel connections.

Unicode TrueType™ fonts support is

standard with the EasyCoder E4.

In fact, 15 scaleable fonts are included, and more fonts in local languages—including Latin and non-Latin—can be downloaded into flash memory or be supported using a PC card.

Intermec's unique EasySet™ System is standard with the EasyCoder E4. The system incorporates a bar code interface allowing quick and effortless set-up of media and ribbon parameters, for precise and secured print quality.

The printer is designed on a chassis of reinforced composite materials, and covers consist of Polycarbonate and ABS plastics. These materials are all non-hazardous and recyclable, which also makes the EasyCoder E4 environment friendly.



Intermec

Application

Direct Thermal and Thermal Transfer printer for labels, tickets and tags. Peel-off/Self-Strip with Label-Taken Sensor, plus integral Self-Strip unit with Liner Takeup. Separate LinerLess version for Direct Thermal labels.

Models

EasyCoder E4
EasyCoder E4 LinerLess

Physical Characteristics

Length: 351 mm (13.8 in)
Height: 170 mm (6.7 in)
Width: 236 mm (9.3 in)
Weight: 4.7 kg (10.4 lbs)

Print Specifications

Print Width:
Max. 104 mm (4.09 in)

Print Speed:

Max. 152.4 mm/s (6 in/s)

Print Direction:

Prints text, bar codes, and crisp graphics in all four directions.

Print Resolution:

203 dpi (8 dots/mm)

Media Specifications**Label Size –**

Max. width: 114 mm (4.5 in)
Min. length: 10 mm (0.4 in)
Max. length: unlimited

Label/Ribbon Roll –

Label roll: max. diam. 152.4 mm (6 in)
=approx. 101 m of labels (4 000 in)

Ribbon roll: max. diam. 59 mm (2.3 in)
=approx. 203 m of ribbon (8 000 in)

Media core: 38-40 mm (1.5–1.6 in)
or 76 mm (3 in)

Media/Ribbon Characteristics –

Style: Roll-fed, die-cut, continuous, or fanfold labels, tags or tickets, or LinerLess labels

Type: Plain paper thermal transfer or thermal sensitive papers

Ribbon type: wax, wax/resin, resin

Paper and Ribbon Set-up

EasySet™ System–built-in bar code wand interface offers instant printer setting for various papers, ribbons and other printer parameters.

Connect & Print™

Intermec's Connect & Print™ package contains: LabelShop® START Label Design & Print software, InterDriver™ with ActiveX® controls Windows™ driver, parallel computer connection cable, and sample roll of labels and ribbon.

Memory

Standard: 1MB FLASH; 512K DRAM;
2 PC card slots

Interface

Standard: RS-232, Centronics® parallel
Baud Rate: 300–38400

Software

Printer language: Intermec Direct Protocol.

Shipped with InterDriver Windows printer driver for Windows 3.11, Windows 95, 98, NT and 2000 to be used with standard Windows applications, such as Word, Access etc.

Also compatible with Windows label design packages, such as Intermec LabelShop and a wide range of software from independent software vendors.

Bar Code Symbolologies

Incorporates 38 bar code symbolologies, including 2-Dimensional codes like Maxicode and PDF417.

Characters/Fonts

15 scaleable Unicode TrueType™ fonts: Swiss 721 BT, Prestige 12 Pitch Bold BT, Zurich Extra Condensed BT, Swiss 721 Bold BT, Dutch 801 Roman BT, Swiss 721 Bold Condensed BT, Dutch 801 Bold BT, Century Schoolbook BT, Futura Light BT, Letter Gothic 12 Pitch BT, Mono-space 821 BT, Monospace 821 Bold BT, OCR-A BT, OCR-B 10 Pitch BT, and Zapf Dingbats BT.

Text can be smoothly printed at any size.

Optional TrueType fonts on PC card for Eastern Europe, Middle East and Asia (Chinese, Japanese, Korean), Latin and non-Latin characters.

Environment

+5° to +40°C (+40° to +104°F)

Humidity

20–80% RH non condensing

Power Supply

115 or 230V AC (+10%, -15%),
50 or 60 Hz

Operator Control

1 three-colored LED indicator lamp and
1 Print/Feed key

Regulatory Approvals

CE (EN55022 Class A), FCC Class A, UL,
CSA, C-Tick

Options

Real Time Clock, Cutter for tickets and tags (not for linerless material), QR bar code (free of charge), RS-232 cable.

North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

Systems & Solutions

550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies
9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

**Europe/
Middle East & Africa**

Headquarters
Sovereign House
Vastern Road
Reading, Berkshire RG1 8BT
United Kingdom
tel: +44.118.987.9400
fax: +44.118.987.9401

Gothenburg
Idrottsvägen 10
PO Box 123
SE-431 22 Mölndal
Sweden
tel: +46.31.869500
fax: +46.31.869595

**Asia/
Latin America**

Hong Kong
26-12 Shell Tower
Times Square
1 Matheson Street
Causeway Bay
Hong Kong
tel: 852.2574.9777
fax: 852.2574.9725

Singapore

25-16 International Plaza
10 Anson Road, 079903
tel: 65.324.8391
fax: 65.324.8393

Australia

Level 7, 200 Pacific Highway
Crows Nest NSW 2065
Australia
tel: 61.2.9901.2065
fax: 61.2.9954.6300

South America and Mexico

2572 White Road
Irvine, California 92614
tel: 949.975.1905
fax: 949.975.1913

Worldwide

**Fax Document
Retrieval Service**
800.755.5505
(North America Only)
tel: 650.556.8447

Internet

www.intermec.com

Sales

800.347.2636
(toll free in N.A.)
tel: 425.348.2726

Service and Support

800.755.5505
(toll free in N.A.)
tel: 425.356.1799

Copyright © 2001 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 609080-01B 08/01

In a continuing effort to improve our products Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.