ACCESSIBI-LITY FOR YOUR H⊻ME

Aritco HomeLift Access

Datasheet 2021

Aritco HomeLift Access is designed to give access to all parts of your house for both you and your family as well as your friends. Practical and smart with sizes for all needs. With an option to personalize it with details such as glass walls, a range of various colours and different materials.

Advantages offered by Aritco HomeLift Access:

- Design, sizes and options created for a home environment
- Minimum interventions in the house
- Option for a "half-height door" on the top floor
- 'A' rated energy consumption according to VDI4707
- 95% recyclable materials
- Patented screw/nut technology (no oil that can leak)
- The lowest maintenance and operating costs on the market
- Equipped with our SmartSafety system with safety features for home environments.

For more information please visit aritco.com











Aritco Lift AB Elektronikhöjden 14, Box 516 175 26 Järfälla, Sweden T: +46 (0) 8 120 401 00 E: info@aritco.com www.aritco.com

LIFT COLOUR

Can be painted in any RAL colour from the Chart K7 classic chart (except for pearl and fluorescent colours).

DOORS

4 different door types to choose from. Large glass door, double hinged glass door,

GLASS







FLOOR

choose from.





















Size: 900 x 1040 mm Rated load: 250 kg / 2 pers. Wheelchair: -




Size: 900 x 1480 mm Rated load: 410 kg / 5 pers. Wheelchair: A or B with attendent*




Size: 1000 x 1480 mm Rated load: 410 kg / 5 pers. Wheelchair: A or B with attendent*




Size: 1000 x 1980 mm Rated load: 500 kg / 6 pers. Wheelchair: A or B with attendent*




Size: 900 x 1280 mm Rated load: 410 kg / 5 pers. Wheelchair: Lone user or type A*



Size: 1000 x 1280 mm Rated load: 410 kg / 5 pers. Wheelchair: Lone user or type A*



Size: 1100 x 1480 mm Rated load: 410 kg / 5 pers. Wheelchair: A or B with attendent, adjacent entry*



Size: 1100 x 1580 mm **Rated load:** 500 kg / 6 pers. Wheelchair: A or B with attendent, adjacent entry*

TOP HEIGHT

mum mm



INSTALLATION

Recessed installation 50 mm below floor

Installed directly on the floor with 50 mm ramp



Power supply: 230 V 1-phase

TYPE OF LIFT

Home lift intended for installation in Only to be used in build-ings without public access.





Max **0,15 m/s** Max **0,25 m/s**



DRIVE SYSTEM

Patented screw and nut system

TRAVEL HEIGHT

3000 limeter

CONTROL FROM CARRIER CONTROL PANEL

Hold to run - press and hold For installations outside Europe

One touch operation (press one time)





WARRANTY

Aritco HomeLift Access comes with a 24 month warranty The screw and nut assembly has a 10 year warranty.



TECHNICAL COMPLIANCE

European Machine directive 2006/42/EC European standard EN 81-41

Emergency lowering: Battery-powered