



X5400 Range Rack Mount Touch PC

The X5400 Rack Mount Touch Computer Range, Designed to be mounted inside a standard 19" Server or Network Rack. This range of rack mount computers are anchored into the rack mount system with cage nuts. This range of touch computers have been specifically created for use within a rack mount enclosure. The standard rack-mount pc is for 19" 4 to 8 RU (EIA-310) constructed from steel. The rack mount enclosure is designed for the cable to exit from the bottom and the simple installation uses a standard cage nut system providing a robust solution accessible for easy maintenance, installation and upgrades.

<https://stxtechnology.co.uk/x5400-rack-mount-pc>

X5412

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 12.1" 4:3
Resolution: 1024x768
Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S
System Memory: 8 GB (optional 16GB | 24GB | 40GB)
Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)
Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options
Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options
Touch: USB Touch (optional RS232 Serial)
Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: Carbon Steel
Finish: Powder Coated
Mounting: 19" Rack mount(EIA-310)
Connectors: 3 Pin Power Connector
Power Input: 10VDC~30VDC (optional 110~240VAC)

Connectors

USB: 1 x USB
Serial: 1 x RS-232 (optional up to 8 x RS232)
RS485 or RS422
CAN Bus
High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 4 Ethernet 1000Mbps)
WiFi: Dual Band
Bluetooth
3G / 4G LTE or 4G / 5G

Accessories

Mounting: Rack Mount



<https://stxtechnology.co.uk/x5412-121-inch-rack-mount-pc>



Touch Panel PC - Resistive Touch

X5412-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5412-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5412-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5412-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X5412-M-RT

HDMI | VGA | DP
USB Touch

X5412-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Touch Panel PC - Projective Capacitive Touch

X5412-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5412-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5412-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5412-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X5412-M-PT

HDMI | VGA | DP
USB Touch

X5412-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Optional Features

Display Brightness

-High Brightnes 600nits
-High Brightnes 1000nits

Power:

-240VAC
-110VAC
-Other voltages

System:

-256GB | 512GB | 1TB | 2TB
-Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
-RS485
-CAN bus
-High Speed Serial (to 3M Baud)
-3G / 4G or 4G / 5G

Material:

-Steel

Mounting:

-19" Standard Mount

Finish:

-Carbon Steel Brushed
-Steel Electro Polished
-Matte Black

<https://stxtechnology.co.uk/x5412-121-inch-rack-mount-pc>

X5415

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 15" 4:3

Resolution: 1024x768

Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S

System Memory: 8 GB (optional 16GB | 24GB | 40GB)

Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)

Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: Carbon Steel

Finish: Powder Coated

Mounting: 19" Rack mount(EIA-310)

Connectors: 3 Pin Power Connector

Power Input: 10VDC~30VDC (optional 110~240VAC)

Connectors

USB: 1 x USB

Serial: 1 x RS-232 (optional up to 8 x RS232)

RS485 or RS422

CAN Bus

High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 4 Ethernet 1000Mbps)

WiFi: Dual Band

Bluetooth

3G / 4G LTE or 4G / 5G

Accessories

Mounting: Rack Mount



<https://stxtechnology.co.uk/x5415-15-inch-industrial-touch-panel-pc>



Touch Panel PC - Resistive Touch

X5415-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5415-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5415-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5415-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X5415-M-RT

HDMI | VGA | DP
USB Touch

X5415-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Touch Panel PC - Projective Capacitive Touch

X5415-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5415-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5415-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5415-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X5415-M-PT

HDMI | VGA | DP
USB Touch

X5415-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Optional Features

Display Brightness

-High Brightnes 600nits
-High Brightnes 1000nits

Power:

-240VAC
-110VAC
-Other voltages

System:

-256GB | 512GB | 1TB | 2TB
-Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
-RS485
-CAN bus
-High Speed Serial (to 3M Baud)
-3G / 4G or 4G / 5G

Material:

-Steel

Mounting:

-19" Standard Mount

Finish:

-Carbon Steel Brushed
-Steel Electro Polished
-Matte Black

<https://stxtechnology.co.uk/x5415-15-inch-industrial-touch-panel-pc>

X5416

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 15.6" 16.9
Resolution: 1920x1080
Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S
System Memory: 8 GB (optional 16GB | 24GB | 40GB)
Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)
Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options
Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options
Touch: USB Touch (optional RS232 Serial)
Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: Carbon Steel
Finish: Powder Coated
Mounting: 19" Rack mount(EIA-310)
Connectors: 3 Pin Power Connector
Power Input: 10VDC~30VDC (optional 110~240VAC)

Connectors

USB: 1 x USB
Serial: 1 x RS-232 (optional up to 8 x RS232)
RS485 or RS422
CAN Bus
High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 4 Ethernet 1000Mbps)
WiFi: Dual Band
Bluetooth
3G / 4G LTE or 4G / 5G

Accessories

Mounting: Rack Mount



<https://stxtechnology.co.uk/x5416-156-inch-rack-mount-touch-panel-pc>



Touch Panel PC - Resistive Touch

X5416-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5416-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5416-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5416-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X5416-M-RT

HDMI | VGA | DP
USB Touch

X5416-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Touch Panel PC - Projective Capacitive Touch

X5416-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5416-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5416-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5416-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X5416-M-PT

HDMI | VGA | DP
USB Touch

X5416-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Optional Features

Display Brightness

-High Brightnes 600nits
-High Brightnes 1000nits

Power:

-240VAC
-110VAC
-Other voltages

System:

-256GB | 512GB | 1TB | 2TB
-Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 / RS485
-CAN bus
-High Speed Serial (to 3M Baud)
-3G / 4G or 4G / 5G

Material:

-Steel

Mounting:

-19" Standard Mount

Finish:

-Carbon Steel Brushed
-Steel Electro Polished
-Matte Black

<https://stxtechnology.co.uk/x5416-156-inch-rack-mount-touch-panel-pc>

X5417

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 17" 5:4

Resolution: 1280x1024

Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S

System Memory: 8 GB (optional 16GB | 24GB | 40GB)

Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)

Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: Carbon Steel

Finish: Powder Coated

Mounting: 19" Rack mount(EIA-310)

Connectors: 3 Pin Power Connector

Power Input: 10VDC~30VDC (optional 110~240VAC)

Connectors

USB: 1 x USB

Serial: 1 x RS-232 (optional up to 8 x RS232)

RS485 or RS422

CAN Bus

High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 4 Ethernet 1000Mbps)

WiFi: Dual Band

Bluetooth

3G / 4G LTE or 4G / 5G

Accessories

Mounting: Rack Mount



<https://stxtechnology.co.uk/x5417-17-inch-rack-mount-touch-panel-pc>



Touch Panel PC - Resistive Touch

X5417-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5417-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5417-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5417-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X5417-M-RT

HDMI | VGA | DP
USB Touch

X5417-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Touch Panel PC - Projective Capacitive Touch

X5417-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5417-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5417-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5417-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X5417-M-PT

HDMI | VGA | DP
USB Touch

X5417-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Optional Features

Display Brightness

-High Brightnes 600nits
-High Brightnes 1000nits

Power:

-240VAC
-110VAC
-Other voltages

System:

-256GB | 512GB | 1TB | 2TB
-Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
-RS485
-CAN bus
-High Speed Serial (to 3M Baud)
-3G / 4G or 4G / 5G

Material:

-Steel

Mounting:

-19" Standard Mount

Finish:

-Carbon Steel Brushed
-Steel Electro Polished
-Matte Black

<https://stxtechnology.co.uk/x5417-17-inch-rack-mount-touch-panel-pc>

X5418

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 18.5" 16.9
Resolution: 1920x1080
Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S
System Memory: 8 GB (optional 16GB | 24GB | 40GB)
Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)
Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options
Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options
Touch: USB Touch (optional RS232 Serial)
Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: Carbon Steel
Finish: Powder Coated
Mounting: 19" Rack mount(EIA-310)
Connectors: 3 Pin Power Connector
Power Input: 10VDC~30VDC (optional 110~240VAC)

Connectors

USB: 1 x USB
Serial: 1 x RS-232 (optional up to 8 x RS232)
RS485 or RS422
CAN Bus
High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 4 Ethernet 1000Mbps)
WiFi: Dual Band
Bluetooth
3G / 4G LTE or 4G / 5G

Accessories

Mounting: Rack Mount



<https://stxtechnology.co.uk/x5418-185-inch-rack-mount-touch-panel-pc>



Touch Panel PC - Resistive Touch

X5418-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5418-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5418-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5418-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X5418-M-RT

HDMI | VGA | DP
USB Touch

X5418-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Touch Panel PC - Projective Capacitive Touch

X5418-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5418-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5418-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5418-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X5418-M-PT

HDMI | VGA | DP
USB Touch

X5418-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Optional Features

Display Brightness

-High Brightnes 600nits
-High Brightnes 1000nits

Power:

-240VAC
-110VAC
-Other voltages

System:

-256GB | 512GB | 1TB | 2TB
-Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
-RS485
-CAN bus
-High Speed Serial (to 3M Baud)
-3G / 4G or 4G / 5G

Material:

-Steel

Mounting:

-19" Standard Mount

Finish:

-Carbon Steel Brushed
-Steel Electro Polished
-Matte Black

<https://stxtechnology.co.uk/x5418-185-inch-rack-mount-touch-panel-pc>

X5419

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 19" 5:4

Resolution: 1280x1024

Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S

System Memory: 8 GB (optional 16GB | 24GB | 40GB)

Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)

Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: Carbon Steel

Finish: Powder Coated

Mounting: 19" Rack mount(EIA-310)

Connectors: 3 Pin Power Connector

Power Input: 10VDC~30VDC (optional 110~240VAC)

Connectors

USB: 1 x USB

Serial: 1 x RS-232 (optional up to 8 x RS232)

RS485 or RS422

CAN Bus

High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 4 Ethernet 1000Mbps)

WiFi: Dual Band

Bluetooth

3G / 4G LTE or 4G / 5G

Accessories

Mounting: Rack Mount



<https://stxtechnology.co.uk/x5419-19-inch-rack-mount-pc>



Touch Panel PC - Resistive Touch

X5419-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5419-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5419-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5419-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X5419-M-RT

HDMI | VGA | DP
USB Touch

X5419-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Touch Panel PC - Projective Capacitive Touch

X5419-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5419-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5418-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X5418-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X5418-M-PT

HDMI | VGA | DP
USB Touch

X5418-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Optional Features

Display Brightness

-High Brightnes 600nits
-High Brightnes 1000nits

Power:

-240VAC
-110VAC
-Other voltages

System:

-256GB | 512GB | 1TB | 2TB
-Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
-RS485
-CAN bus
-High Speed Serial (to 3M Baud)
-3G / 4G or 4G / 5G

Material:

-Steel

Mounting:

-19" Standard Mount

Finish:

-Carbon Steel Brushed
-Steel Electro Polished
-Matte Black

<https://stxtechnology.co.uk/x5419-19-inch-rack-mount-pc>