



OPAL



MICROPRISM



### DIMENSIONS



L, mm	W, mm	H, mm
1135	58	75
1415		

**LISOS** provides an attractive and cost effective solution for linear aluminium extruded systems. Suitable for suspended up/down or surface mount applications and available in two body lengths with varying lumen output options. Finished light grey RAL9006 as standard with RAL colour options. Opal polycarbonate or Linear Microprism optics. Colour temperature 4000K.

Product Code	Description	Weight
LIS30/OP	LISOS 1135mm 30W 3604 lumen opal	2.7kg
LIS44/OP	LISOS 1135mm 44W 4953 lumen opal	2.7kg
LIS38/OP	LISOS 1415mm 38W 4622 lumen opal	3.2kg
LIS55/OP	LISOS 1415mm 55W 6354 lumen opal	3.2kg
LIS30/MP	LISOS 1135mm 30W 3327 lumen microprism	2.7kg
LIS44/MP	LISOS 1135mm 44W 4572 lumen microprism	2.7kg
LIS38/MP	LISOS 1415mm 38W 4276 lumen microprism	3.2kg
LIS55/MP	LISOS 1415mm 55W 5878 lumen microprism	3.2kg
/ E3	Integral 3hr emergency	
/ DD	DALI control	

### Options

- Continuous runs with in-line connection
- 3000K
- RAL colours
- Opal Polycarbonate or Linear Microprism polycarbonate optic
- Suspended or Surface mount
- Integrated smart sensor for wireless control

### Features

- Slim unobtrusive profile
- 50,000hr L80B20
- Colour and output options