



X7500 Range Industrial Panel PC - Waterproof

STX Technology's X7500 Stainless Steel Touch Panel PC is engineered for tough and rugged environments with IP67 / IP68 (NEMA 6 / NEMA 6P) connectors, Resistive or Projective Capacitive (PCAP) Touch options and multiple CPU options. offers a cutting-edge solution for various industries, particularly excelling in the demanding environments of food processing in the UK. With optional protective membranes, they can endure user damage, providing added resilience. optional operating systems Windows, Linux, or Android—these computers are remarkably versatile and reliable. In essence, the X7500 Series seamlessly blends innovation with reliability, meeting the rigorous demands of multiple industries, notably excelling in the realm of food processing in the UK.

<https://stxtechnology.co.uk/x7500-range-industrial-panel-pcs>

X7508

Touch

Touch Type: Resistive Touch

Display

LCD Size: 8.4" 4:3

Resolution: 800x600

Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S

System Memory: 8 GB (optional 16GB | 24GB | 40GB)

Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)

Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: 304 Stainless Steel (optional 316 Stainless Steel)

Finish: Brushed (optional Highly Polished)

Mounting: M10 Side Mounts (optional VESA, other)

Connectors: IP67 / IP68

Power Input: 10VDC~30VDC (optional 110~240VAC)

Display Protector: Tough Sacrificial Touch Membrane

Ports

USB: 1 x USB

Serial: 1 x RS-232 (optional up to 8 x RS232)

RS485 or RS422

CAN Bus

High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 3 Ethernet 1000Mbps)

WiFi: Dual Band

Bluetooth

3G / 4G LTE or 4G / 5G

Accessories

Keyboard Optional IP68 Keyboard and Keyboard Tray Kit

Mounting Options Various mounting kits available including top side and wall mounting

<https://stxtechnology.co.uk/x7508-8-industrial-touch-panel-pc>





Touch Panel PC

X7508-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7508-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7508-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7508-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor

X7508-M-RT

HDMI | VGA | DP
USB Touch

X7508-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Optional Features

Display Brightness

-High Brightnes 600nits
-High Brightnes 1000nits

Power:

-240VAC
-110VAC
-Other voltages

System:

-256GB | 512GB | 1TB | 2TB
-Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
-RS485
-CAN bus
-High Speed Serial (to 3M Baud)
-3G / 4G or 4G / 5G

Material:

-304 Stainless Steel
-316 Stainless Steel

Mounting:

-VESA Mount

Finish:

-Stainless Steel Brushed
-Stainless Steel Highly Polished
-Stainless Steel Electro Polished
-Matte Black

Display Protector:

-Sacrificial Touch Membrane

<https://stxtechnology.co.uk/x7508-8-industrial-touch-panel-pc>

X7510

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 10.4" 4:3

Resolution: 1024x768

Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S

System Memory: 8 GB (optional 16GB | 24GB | 40GB)

Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)

Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: 304 Stainless Steel (optional 316 Stainless Steel)

Finish: Brushed (optional Highly Polished)

Mounting: M10 Side Mounts (optional VESA, other)

Connectors: IP67 / IP68

Power Input: 10VDC~30VDC (optional 110~240VAC)

Display Protector: Tough Sacrificial Touch Membrane

Ports

USB: 1 x USB

Serial: 1 x RS-232 (optional up to 8 x RS232)

RS485 or RS422

CAN Bus

High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 3 Ethernet 1000Mbps)

WiFi: Dual Band

Bluetooth

3G / 4G LTE or 4G / 5G

Accessories

Keyboard Optional IP68 Keyboard and Keyboard Tray Kit

Mounting Options Various mounting kits available including top side and wall mounting

<https://stxtechnology.co.uk/x7510-10-industrial-touch-panel-pc>





Touch Panel PC - Resistive Touch

X7510-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7510-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7510-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7510-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X7510-M-RT

HDMI | VGA | DP
USB Touch

X7510-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Touch Panel PC - Projective Capacitive Touch

X7510-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7510-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7510-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7510-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X7510-M-PT

HDMI | VGA | DP
USB Touch

X7510-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Optional Features

Display Brightness

-High Brightnes 600nits
-High Brightnes 1000nits

Power:

-240VAC
-110VAC
-Other voltages

System:

-256GB | 512GB | 1TB | 2TB
-Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
-RS485
-CAN bus
-High Speed Serial (to 3M Baud)
-3G / 4G or 4G / 5G

Material:

-304 Stainless Steel
-316 Stainless Steel

Mounting:

-VESA Mount

Finish:

-Stainless Steel Brushed
-Stainless Steel Highly Polished
-Stainless Steel Electro Polished
-Matte Black

Display Protector:

-Sacrificial Touch Membrane

<https://stxtechnology.co.uk/x7510-10-industrial-touch-panel-pc>

X7510W

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 10.1" 16:9
Resolution: 1280x800
Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S
System Memory: 8 GB (optional 16GB | 24GB | 40GB)
Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)
Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options
Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options
Touch: USB Touch (optional RS232 Serial)
Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: 304 Stainless Steel (optional 316 Stainless Steel)
Finish: Brushed (optional Highly Polished)
Mounting: M10 Side Mounts (optional VESA, other)
Connectors: IP67 / IP68
Power Input: 10VDC~30VDC (optional 110~240VAC)
Display Protector: Tough Sacrificial Touch Membrane

Ports

USB: 1 x USB
Serial: 1 x RS-232 (optional up to 8 x RS232)
RS485 or RS422
CAN Bus
High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 3 Ethernet 1000Mbps)
WiFi: Dual Band
Bluetooth
3G / 4G LTE or 4G / 5G

Accessories

Keyboard Optional IP68 Keyboard and Keyboard Tray Kit
Mounting Options Various mounting kits available including top side and wall mounting



<https://stxtechnology.co.uk/x7510w-10-inch-industrial-touch-panel-pc>



Touch Panel PC - Resistive Touch

X7510W-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7510W-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7510W-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7510W-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X7510W-M-RT

HDMI | VGA | DP
USB Touch

X7510W-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Touch Panel PC - Projective Capacitive Touch

X7510W-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7510W-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7510W-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7510W-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X7510W-M-PT

HDMI | VGA | DP
USB Touch

X7510W-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Optional Features

Display Brightness

-High Brightnes 600nits
-High Brightnes 1000nits

Power:

-240VAC
-110VAC
-Other voltages

System:

-256GB | 512GB | 1TB | 2TB
-Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
-RS485
-CAN bus
-High Speed Serial (to 3M Baud)
-3G / 4G or 4G / 5G

Material:

-304 Stainless Steel
-316 Stainless Steel

Mounting:

-VESA Mount

Finish:

-Stainless Steel Brushed
-Stainless Steel Highly Polished
-Stainless Steel Electro Polished
-Matte Black

Display Protector:

-Sacrificial Touch Membrane

<https://stxtechnology.co.uk/x7510w-10-inch-industrial-touch-panel-pc>

X7512

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 12.1" 4:3

Resolution: 1024x768

Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S

System Memory: 8 GB (optional 16GB | 24GB | 40GB)

Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)

Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: 304 Stainless Steel (optional 316 Stainless Steel)

Finish: Brushed (optional Highly Polished)

Mounting: M10 Side Mounts (optional VESA, other)

Connectors: IP67 / IP68

Power Input: 10VDC~30VDC (optional 110~240VAC)

Display Protector: Tough Sacrificial Touch Membrane

Ports

USB: 1 x USB

Serial: 1 x RS-232 (optional up to 8 x RS232)

RS485 or RS422

CAN Bus

High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 3 Ethernet 1000Mbps)

WiFi: Dual Band

Bluetooth

3G / 4G LTE or 4G / 5G

Accessories

Keyboard Optional IP68 Keyboard and Keyboard Tray Kit

Mounting Options Various mounting kits available including top side and wall mounting



<https://stxtechnology.co.uk/x7512-12-industrial-touch-panel-pc>

Order Options



Touch Panel PC - Resistive Touch

X7512-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7512-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7512-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7512-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X7512-M-RT

HDMI | VGA | DP
USB Touch

X7512-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Touch Panel PC - Projective Capacitive Touch

X7512-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7512-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7512-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7512-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X7512-M-PT

HDMI | VGA | DP
USB Touch

X7512-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Optional Features

Display Brightness

-High Brightnes 600nits
-High Brightnes 1000nits

Power:

-240VAC
-110VAC
-Other voltages

System:

-256GB | 512GB | 1TB | 2TB
-Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
-RS485
-CAN bus
-High Speed Serial (to 3M Baud)
-3G / 4G or 4G / 5G

Material:

-304 Stainless Steel
-316 Stainless Steel

Mounting:

-VESA Mount
-Panel Mount

Finish:

-Stainless Steel Brushed
-Stainless Steel Highly Polished
-Stainless Steel Electro Polished
-Matte Black

Display Protector:

-Sacrificial Touch Membrane

<https://stxtechnology.co.uk/x7512-12-industrial-touch-panel-pc>

X7513

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 13.3" 16:9

Resolution: 1920x1080

Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S

System Memory: 8 GB (optional 16GB | 24GB | 40GB)

Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)

Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: 304 Stainless Steel (optional 316 Stainless Steel)

Finish: Brushed (optional Highly Polished)

Mounting: M10 Side Mounts (optional VESA, other)

Connectors: IP67 / IP68

Power Input: 10VDC~30VDC (optional 110~240VAC)

Display Protector: Tough Sacrificial Touch Membrane

Ports

USB: 1 x USB

Serial: 1 x RS-232 (optional up to 8 x RS232)

RS485 or RS422

CAN Bus

High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 3 Ethernet 1000Mbps)

WiFi: Dual Band

Bluetooth

3G / 4G LTE or 4G / 5G

Accessories

Keyboard Optional IP68 Keyboard and Keyboard Tray Kit

Mounting Options Various mounting kits available including top side and wall mounting



<https://stxtechnology.co.uk/x7513-13-inch-industrial-touch-panel-pc>



Touch Panel PC - Resistive Touch

X7513-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7513-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7513-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7513-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X7513-M-RT

HDMI | VGA | DP
USB Touch

X7513-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Touch Panel PC - Projective Capacitive Touch

X7513-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7513-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7513-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7513-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X7513-M-PT

HDMI | VGA | DP
USB Touch

X7513-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Optional Features

Display Brightness

-High Brightnes 600nits
-High Brightnes 1000nits

Power:

-240VAC
-110VAC
-Other voltages

System:

-256GB | 512GB | 1TB | 2TB
-Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
-RS485
-CAN bus
-High Speed Serial (to 3M Baud)
-3G / 4G or 4G / 5G

Material:

-304 Stainless Steel
-316 Stainless Steel

Mounting:

-VESA Mount
-Panel Mount

Finish:

-Stainless Steel Brushed
-Stainless Steel Highly Polished
-Stainless Steel Electro Polished
-Matte Black

Display Protector:

-Sacrificial Touch Membrane

<https://stxtechnology.co.uk/x7513-13-inch-industrial-touch-panel-pc>

X7515

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 15" 4:3

Resolution: 1024x768

Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S

System Memory: 8 GB (optional 16GB | 24GB | 40GB)

Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)

Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: 304 Stainless Steel (optional 316 Stainless Steel)

Finish: Brushed (optional Highly Polished)

Mounting: M10 Side Mounts (optional VESA, other)

Connectors: IP67 / IP68

Power Input: 10VDC~30VDC (optional 110~240VAC)

Display Protector: Tough Sacrificial Touch Membrane

Ports

USB: 1 x USB

Serial: 1 x RS-232 (optional up to 8 x RS232)

RS485 or RS422

CAN Bus

High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 3 Ethernet 1000Mbps)

WiFi: Dual Band

Bluetooth

3G / 4G LTE or 4G / 5G

Accessories

Keyboard Optional IP68 Keyboard and Keyboard Tray Kit

Mounting Options Various mounting kits available including top side and wall mounting



<https://stxtechnology.co.uk/x7515-15-industrial-touch-panel-pc>

Order Options



Touch Panel PC - Resistive Touch

X7515-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7515-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7515-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7515-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X7515-M-RT

HDMI | VGA | DP
USB Touch

X7515-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Touch Panel PC - Projective Capacitive Touch

X7515-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7515-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7515-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7515-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X7515-M-PT

HDMI | VGA | DP
USB Touch

X7515-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Optional Features

Display Brightness

-High Brightnes 600nits
-High Brightnes 1000nits

Power:

-240VAC
-110VAC
-Other voltages

System:

-256GB | 512GB | 1TB | 2TB
-Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
-RS485
-CAN bus
-High Speed Serial (to 3M Baud)
-3G / 4G or 4G / 5G

Material:

-304 Stainless Steel
-316 Stainless Steel

Mounting:

-VESA Mount
-Panel Mount

Finish:

-Stainless Steel Brushed
-Stainless Steel Highly Polished
-Stainless Steel Electro Polished
-Matte Black

Display Protector:

-Sacrificial Touch Membrane

<https://stxtechnology.co.uk/x7515-15-industrial-touch-panel-pc>

X7516

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 15.6" 16:9
Resolution: 1920x1080
Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S
System Memory: 8 GB (optional 16GB | 24GB | 40GB)
Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)
Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options
Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options
Touch: USB Touch (optional RS232 Serial)
Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: 304 Stainless Steel (optional 316 Stainless Steel)
Finish: Brushed (optional Highly Polished)
Mounting: M10 Side Mounts (optional VESA, other)
Connectors: IP67 / IP68
Power Input: 10VDC~30VDC (optional 110~240VAC)
Display Protector: Tough Sacrificial Touch Membrane

Ports

USB: 1 x USB
Serial: 1 x RS-232 (optional up to 8 x RS232)
RS485 or RS422
CAN Bus
High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 3 Ethernet 1000Mbps)
WiFi: Dual Band
Bluetooth
3G / 4G LTE or 4G / 5G

Accessories

Keyboard Optional IP68 Keyboard and Keyboard Tray Kit
Mounting Options Various mounting kits available including top side and wall mounting



<https://stxtechnology.co.uk/x7516-16-inch-industrial-touch-panel-pc>



Touch Panel PC - Resistive Touch

X7516-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7516-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7516-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7516-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X7516-M-RT

HDMI | VGA | DP
USB Touch

X7516-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6



Touch Panel PC - Resistive Touch with built-in Keyboard

X7516-C4-RT-KB

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7516-C5-RT-KB

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7516-C7-RT-KB

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7516-A3-RT-KB

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch with built-in Keyboard

X7516-M-RT-KB

HDMI | VGA | DP
USB Touch

X7516-M-RT-KVM-KB

HDMI | DP & USB Touch
Up to 100M over CAT6

<https://stxtechnology.co.uk/x7516-16-inch-industrial-touch-panel-pc>

Order Options



Touch Panel PC - Projective Capacitive Touch

X7516-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7516-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7516-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7516-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X7516-M-PT

HDMI | VGA | DP
USB Touch

X7516-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6



Touch Panel PC - Projective Capacitive Touch with built-in Keyboard

X7516-C4-RT-KB

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7516-C5-RT-KB

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7516-C7-RT-KB

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7516-A3-RT-KB

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch with built-in Keyboard

X7516-M-RT-KB

HDMI | VGA | DP
USB Touch

X7516-M-RT-KVM-KB

HDMI | DP & USB Touch
Up to 100M over CAT6

<https://stxtechnology.co.uk/x7516-16-inch-industrial-touch-panel-pc>

Contact the STX Team!
Milton Keynes: +44 1908 966099
London: +44 20 3582 7235

Optional Features

Display Brightness

- High Brightnes 600nits
- High Brightnes 1000nits

Power:

- 240VAC
- 110VAC
- Other voltages

System:

- 256GB | 512GB | 1TB | 2TB
- Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
- RS485
- CAN bus
- High Speed Serial (to 3M Baud)
- 3G / 4G or 4G / 5G

Material:

- 304 Stainless Steel
- 316 Stainless Steel

Mounting:

- VESA Mount
- Panel Mount

Finish:

- Stainless Steel Brushed
- Stainless Steel Highly Polished
- Stainless Steel Electro Polished
- Matte Black

Display Protector:

- Sacrificial Touch Membrane

<https://stxtechnology.co.uk/x7516-16-inch-industrial-touch-panel-pc>

X7517

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 17" 4:3

Resolution: 1280x1024

Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S

System Memory: 8 GB (optional 16GB | 24GB | 40GB)

Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)

Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: 304 Stainless Steel (optional 316 Stainless Steel)

Finish: Brushed (optional Highly Polished)

Mounting: M10 Side Mounts (optional VESA, other)

Connectors: IP67 / IP68

Power Input: 10VDC~30VDC (optional 110~240VAC)

Display Protector: Tough Sacrificial Touch Membrane

Ports

USB: 1 x USB

Serial: 1 x RS-232 (optional up to 8 x RS232)

RS485 or RS422

CAN Bus

High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 3 Ethernet 1000Mbps)

WiFi: Dual Band

Bluetooth

3G / 4G LTE or 4G / 5G

Accessories

Keyboard Optional IP68 Keyboard and Keyboard Tray Kit

Mounting Options Various mounting kits available including top side and wall mounting

<https://stxtechnology.co.uk/x7517-17-industrial-touch-panel-pc>



Order Options



Touch Panel PC - Resistive Touch

X7517-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7517-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7517-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7517-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X7517-M-RT

HDMI | VGA | DP
USB Touch

X7517-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Touch Panel PC - Projective Capacitive Touch

X7517-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7517-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7517-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7517-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X7517-M-PT

HDMI | VGA | DP
USB Touch

X7517-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Optional Features

Display Brightness

-High Brightnes 600nits
-High Brightnes 1000nits

Power:

-240VAC
-110VAC
-Other voltages

System:

-256GB | 512GB | 1TB | 2TB
-Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
-RS485
-CAN bus
-High Speed Serial (to 3M Baud)
-3G / 4G or 4G / 5G

Material:

-304 Stainless Steel
-316 Stainless Steel

Mounting:

-VESA Mount
-Panel Mount

Finish:

-Stainless Steel Brushed
-Stainless Steel Highly Polished
-Stainless Steel Electro Polished
-Matte Black

Display Protector:

-Sacrificial Touch Membrane

<https://stxtechnology.co.uk/x7517-17-industrial-touch-panel-pc>

X7518

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 18.5" 16:9
Resolution: 1920x1080
Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S
System Memory: 8 GB (optional 16GB | 24GB | 40GB)
Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)
Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options
Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options
Touch: USB Touch (optional RS232 Serial)
Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: 304 Stainless Steel (optional 316 Stainless Steel)
Finish: Brushed (optional Highly Polished)
Mounting: M10 Side Mounts (optional VESA, other)
Connectors: IP67 / IP68
Power Input: 10VDC~30VDC (optional 110~240VAC)
Display Protector: Tough Sacrificial Touch Membrane

Ports

USB: 1 x USB
Serial: 1 x RS-232 (optional up to 8 x RS232)
RS485 or RS422
CAN Bus
High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 3 Ethernet 1000Mbps)
WiFi: Dual Band
Bluetooth
3G / 4G LTE or 4G / 5G

Accessories

Keyboard Optional IP68 Keyboard and Keyboard Tray Kit
Mounting Options Various mounting kits available including top side and wall mounting

<https://stxtechnology.co.uk/x7518-18-industrial-touch-panel-pc>





Touch Panel PC - Resistive Touch

X7518-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7518-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7518-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7518-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X7518-M-RT

HDMI | VGA | DP
USB Touch

X7518-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6



Touch Panel PC - Resistive Touch with built-in Keyboard

X7518-C4-RT-KB

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7518-C5-RT-KB

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7518-C7-RT-KB

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7518-A3-RT-KB

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch with built-in Keyboard

X7518-M-RT-KB

HDMI | VGA | DP
USB Touch

X7518-M-RT-KVM-KB

HDMI | DP & USB Touch
Up to 100M over CAT6

<https://stxtechnology.co.uk/x7518-18-industrial-touch-panel-pc>

Order Options



Touch Panel PC - Projective Capacitive Touch

X7518-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7518-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7518-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7518-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X7518-M-PT

HDMI | VGA | DP
USB Touch

X7518-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6



Touch Panel PC - Projective Capacitive Touch with built-in Keyboard

X7518-C4-RT-KB

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7518-C5-RT-KB

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7518-C7-RT-KB

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7518-A3-RT-KB

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch with built-in Keyboard

X7518-M-RT-KB

HDMI | VGA | DP
USB Touch

X7518-M-RT-KVM-KB

HDMI | DP & USB Touch
Up to 100M over CAT6

<https://stxtechnology.co.uk/x7518-18-industrial-touch-panel-pc>

Contact the STX Team!
Milton Keynes: +44 1908 966099
London: +44 20 3582 7235

Optional Features

Display Brightness

- High Brightnes 600nits
- High Brightnes 1000nits

Power:

- 240VAC
- 110VAC
- Other voltages

System:

- 256GB | 512GB | 1TB | 2TB
- Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
- RS485
- CAN bus
- High Speed Serial (to 3M Baud)
- 3G / 4G or 4G / 5G

Material:

- 304 Stainless Steel
- 316 Stainless Steel

Mounting:

- VESA Mount
- Panel Mount

Finish:

- Stainless Steel Brushed
- Stainless Steel Highly Polished
- Stainless Steel Electro Polished
- Matte Black

Display Protector:

- Sacrificial Touch Membrane

<https://stxtechnology.co.uk/x7518-18-industrial-touch-panel-pc>

X7519

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 19" 4:3

Resolution: 1280x1024

Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S

System Memory: 8 GB (optional 16GB | 24GB | 40GB)

Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)

Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: 304 Stainless Steel (optional 316 Stainless Steel)

Finish: Brushed (optional Highly Polished)

Mounting: M10 Side Mounts (optional VESA, other)

Connectors: IP67 / IP68

Power Input: 10VDC~30VDC (optional 110~240VAC)

Display Protector: Tough Sacrificial Touch Membrane

Ports

USB: 1 x USB

Serial: 1 x RS-232 (optional up to 8 x RS232)

RS485 or RS422

CAN Bus

High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 3 Ethernet 1000Mbps)

WiFi: Dual Band

Bluetooth

3G / 4G LTE or 4G / 5G

Accessories

Keyboard Optional IP68 Keyboard and Keyboard Tray Kit

Mounting Options Various mounting kits available including top side and wall mounting

<https://stxtechnology.co.uk/x7519-19-industrial-touch-panel-pc>



Order Options



Touch Panel PC - Resistive Touch

X7519-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7519-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7519-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7519-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X7519-M-RT

HDMI | VGA | DP
USB Touch

X7519-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Touch Panel PC - Projective Capacitive Touch

X7519-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7519-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7519-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7519-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X7519-M-PT

HDMI | VGA | DP
USB Touch

X7519-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6

Optional Features

Display Brightness

-High Brightnes 600nits
-High Brightnes 1000nits

Power:

-240VAC
-110VAC
-Other voltages

System:

-256GB | 512GB | 1TB | 2TB
-Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
-RS485
-CAN bus
-High Speed Serial (to 3M Baud)
-3G / 4G or 4G / 5G

Material:

-304 Stainless Steel
-316 Stainless Steel

Mounting:

-VESA Mount
-Panel Mount

Finish:

-Stainless Steel Brushed
-Stainless Steel Highly Polished
-Stainless Steel Electro Polished
-Matte Black

Display Protector:

-Sacrificial Touch Membrane

<https://stxtechnology.co.uk/x7519-19-industrial-touch-panel-pc>

X7522

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 21.5" 16:9
Resolution: 1920x1080
Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S
System Memory: 8 GB (optional 16GB | 24GB | 40GB)
Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)
Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options
Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options
Touch: USB Touch (optional RS232 Serial)
Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: 304 Stainless Steel (optional 316 Stainless Steel)
Finish: Brushed (optional Highly Polished)
Mounting: M10 Side Mounts (optional VESA, other)
Connectors: IP67 / IP68
Power Input: 10VDC~30VDC (optional 110~240VAC)
Display Protector: Tough Sacrificial Touch Membrane

Ports

USB: 1 x USB
Serial: 1 x RS-232 (optional up to 8 x RS232)
RS485 or RS422
CAN Bus
High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 3 Ethernet 1000Mbps)
WiFi: Dual Band
Bluetooth
3G / 4G LTE or 4G / 5G

Accessories

Keyboard Optional IP68 Keyboard and Keyboard Tray Kit
Mounting Options Various mounting kits available including top side and wall mounting



<https://stxtechnology.co.uk/x7522-22-industrial-touch-panel-pc>



Touch Panel PC - Resistive Touch

X7522-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7522-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7522-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7522-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X7522-M-RT

HDMI | VGA | DP
USB Touch

X7522-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6



Touch Panel PC - Resistive Touch with built-in Keyboard

X7522-C4-RT-KB

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7522-C5-RT-KB

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7522-C7-RT-KB

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7522-A3-RT-KB

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch with built-in Keyboard

X7522-M-RT-KB

HDMI | VGA | DP
USB Touch

X7522-M-RT-KVM-KB

HDMI | DP & USB Touch
Up to 100M over CAT6

<https://stxtechnology.co.uk/x7522-22-industrial-touch-panel-pc>

Order Options



Touch Panel PC - Projective Capacitive Touch

X7522-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7522-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7522-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7522-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X7522-M-PT

HDMI | VGA | DP
USB Touch

X7522-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6



Touch Panel PC - Projective Capacitive Touch with built-in Keyboard

X7522-C4-RT-KB

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7522-C5-RT-KB

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7522-C7-RT-KB

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7522-A3-RT-KB

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch with built-in Keyboard

X7522-M-RT-KB

HDMI | VGA | DP
USB Touch

X7522-M-RT-KVM-KB

HDMI | DP & USB Touch
Up to 100M over CAT6

<https://stxtechnology.co.uk/x7522-22-industrial-touch-panel-pc>

Contact the STX Team!
Milton Keynes: +44 1908 966099
London: +44 20 3582 7235

Optional Features

Display Brightness

- High Brightnes 600nits
- High Brightnes 1000nits

Power:

- 240VAC
- 110VAC
- Other voltages

System:

- 256GB | 512GB | 1TB | 2TB
- Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
- RS485
- CAN bus
- High Speed Serial (to 3M Baud)
- 3G / 4G or 4G / 5G

Material:

- 304 Stainless Steel
- 316 Stainless Steel

Mounting:

- VESA Mount
- Panel Mount

Finish:

- Stainless Steel Brushed
- Stainless Steel Highly Polished
- Stainless Steel Electro Polished
- Matte Black

Display Protector:

- Sacrificial Touch Membrane

<https://stxtechnology.co.uk/x7522-22-industrial-touch-panel-pc>

X7524

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 24" 16:9 or 16:10

Resolution: 1920x1080 (Optional 16:10 1920x1200)

Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S

System Memory: 8 GB (optional 16GB | 24GB | 40GB)

Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)

Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options

Touch: USB Touch (optional RS232 Serial)

Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: 304 Stainless Steel (optional 316 Stainless Steel)

Finish: Brushed (optional Highly Polished)

Mounting: M10 Side Mounts (optional VESA, other)

Connectors: IP67 / IP68

Power Input: 10VDC~30VDC (optional 110~240VAC)

Display Protector: Tough Sacrificial Touch Membrane

Ports

USB: 1 x USB

Serial: 1 x RS-232 (optional up to 8 x RS232)

RS485 or RS422

CAN Bus

High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 3 Ethernet 1000Mbps)

WiFi: Dual Band

Bluetooth

3G / 4G LTE or 4G / 5G

Accessories

Keyboard Optional IP68 Keyboard and Keyboard Tray Kit

Mounting Options Various mounting kits available including top side and wall mounting

<https://stxtechnology.co.uk/x7524-24-inch-industrial-touch-panel-pc>





Touch Panel PC - Resistive Touch

X7524-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7524-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7524-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7524-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X7524-M-RT

HDMI | VGA | DP
USB Touch

X7524-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6



Touch Panel PC - Resistive Touch with built-in Keyboard

X7524-C4-RT-KB

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7524-C5-RT-KB

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7524-C7-RT-KB

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7524-A3-RT-KB

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch with built-in Keyboard

X7524-M-RT-KB

HDMI | VGA | DP
USB Touch

X7524-M-RT-KVM-KB

HDMI | DP & USB Touch
Up to 100M over CAT6

<https://stxtechnology.co.uk/x7524-24-inch-industrial-touch-panel-pc>

Order Options



Touch Panel PC - Projective Capacitive Touch

X7524-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7524-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7524-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7524-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X7524-M-PT

HDMI | VGA | DP
USB Touch

X7524-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6



Touch Panel PC - Projective Capacitive Touch with built-in Keyboard

X7524-C4-RT-KB

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7524-C5-RT-KB

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7524-C7-RT-KB

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7524-A3-RT-KB

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch with built-in Keyboard

X7524-M-RT-KB

HDMI | VGA | DP
USB Touch

X7524-M-RT-KVM-KB

HDMI | DP & USB Touch
Up to 100M over CAT6

<https://stxtechnology.co.uk/x7524-24-inch-industrial-touch-panel-pc>

Contact the STX Team!
Milton Keynes: +44 1908 966099
London: +44 20 3582 7235

Optional Features

Display Brightness

- High Brightnes 600nits
- High Brightnes 1000nits

Power:

- 240VAC
- 110VAC
- Other voltages

System:

- 256GB | 512GB | 1TB | 2TB
- Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
- RS485
- CAN bus
- High Speed Serial (to 3M Baud)
- 3G / 4G or 4G / 5G

Material:

- 304 Stainless Steel
- 316 Stainless Steel

Mounting:

- VESA Mount
- Panel Mount

Finish:

- Stainless Steel Brushed
- Stainless Steel Highly Polished
- Stainless Steel Electro Polished
- Matte Black

Display Protector:

- Sacrificial Touch Membrane

<https://stxtechnology.co.uk/x7524-24-inch-industrial-touch-panel-pc>

X7527

Touch

Touch Type: Resistive Touch | Projective Capacitive Touch

Display

LCD Size: 27" 16:9
Resolution: 1920x1080
Brightness (Typical): 400 nits

System

CPU: Intel® Celeron® 6305U | Intel® Core™ i5-1135G7 | Intel® Core™ i7-1165G7 | ARM RK3588S
System Memory: 8 GB (optional 16GB | 24GB | 40GB)
Hard Drive: 128GB Industrial SSD (optional 256GB | 512GB)
Operating systems: Windows 10 | Windows 11 | Linux | Android

Monitor Option

Video Input: HDMI / DVI / VGA / Display Port options
Touch: USB Touch (optional RS232 Serial)

KVM Monitor Option

Video Input: HDMI / VGA / Display Port options
Touch: USB Touch (optional RS232 Serial)
Single CAT6 Cable Video & Touch up to 100M

Mechanical & Environmental

Material: 304 Stainless Steel (optional 316 Stainless Steel)
Finish: Brushed (optional Highly Polished)
Mounting: M10 Side Mounts (optional VESA, other)
Connectors: IP67 / IP68
Power Input: 10VDC~30VDC (optional 110~240VAC)
Display Protector: Tough Sacrificial Touch Membrane

Ports

USB: 1 x USB
Serial: 1 x RS-232 (optional up to 8 x RS232)
RS485 or RS422
CAN Bus
High Speed Serial RS232/RS422/RS485 (to 3M Baud)

Connectivity

Ethernet: 1x 1000Mbps (optional up to 3 Ethernet 1000Mbps)
WiFi: Dual Band
Bluetooth
3G / 4G LTE or 4G / 5G

Accessories

Keyboard Optional IP68 Keyboard and Keyboard Tray Kit
Mounting Options Various mounting kits available including top side and wall mounting

<https://stxtechnology.co.uk/x7527-27-inch-industrial-touch-panel-pc>





Touch Panel PC - Resistive Touch

X7527-C4-RT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7527-C5-RT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7527-C7-RT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7527-A3-RT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch

X7527-M-RT

HDMI | VGA | DP
USB Touch

X7527-M-RT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6



Touch Panel PC - Resistive Touch with built-in Keyboard

X7527-C4-RT-KB

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7527-C5-RT-KB

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7527-C7-RT-KB

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7527-A3-RT-KB

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Resistive Touch with built-in Keyboard

X7527-M-RT-KB

HDMI | VGA | DP
USB Touch

X7527-M-RT-KVM-KB

HDMI | DP & USB Touch
Up to 100M over CAT6

<https://stxtechnology.co.uk/x7527-27-inch-industrial-touch-panel-pc>

Order Options



Touch Panel PC - Projective Capacitive Touch

X75127-C4-PT

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7527-C5-PT

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7527-C7-PT

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7527-A3-PT

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch

X7527-M-PT

HDMI | VGA | DP
USB Touch

X7527-M-PT-KVM

HDMI | DP & USB Touch
Up to 100M over CAT6



Touch Panel PC - Projective Capacitive Touch with built-in Keyboard

X7527-C4-RT-KB

Intel® Celeron® 6305U
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7527-C5-RT-KB

Intel® Core™ i5-1135G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7527-C7-RT-KB

Intel® Core™ i7-1165G7
8GB DDR4 RAM
120GB SSD
Windows | Linux

X7527-A3-RT-KB

ARM RK3588S
8GB DDR4 RAM
128GB EMMC
Android 13

Touch Panel Monitor - Projective Capacitive Touch with built-in Keyboard

X7527-M-RT-KB

HDMI | VGA | DP
USB Touch

X7527-M-RT-KVM-KB

HDMI | DP & USB Touch
Up to 100M over CAT6

<https://stxtechnology.co.uk/x7527-27-inch-industrial-touch-panel-pc>

Contact the STX Team!
Milton Keynes: +44 1908 966099
London: +44 20 3582 7235

Optional Features

Display Brightness

- High Brightnes 600nits
- High Brightnes 1000nits

Power:

- 240VAC
- 110VAC
- Other voltages

System:

- 256GB | 512GB | 1TB | 2TB
- Up to 4 Ethernet 1000Mbps
Up to 8 RS232 / RS422 /
- RS485
- CAN bus
- High Speed Serial (to 3M Baud)
- 3G / 4G or 4G / 5G

Material:

- 304 Stainless Steel
- 316 Stainless Steel

Mounting:

- VESA Mount
- Panel Mount

Finish:

- Stainless Steel Brushed
- Stainless Steel Highly Polished
- Stainless Steel Electro Polished
- Matte Black

Display Protector:

- Sacrificial Touch Membrane

<https://stxtechnology.co.uk/x7527-27-inch-industrial-touch-panel-pc>