

PRODUCT CONFIGURATIONS



D-6484

BEV-CON™ Flexible Screw Conveyor for difficult-to-handle bulk materials



USA

FLEXICON CORPORATION
2400 Emrick Boulevard
Bethlehem, PA 18020-8006
USA
Tel: 1 888 FLEXICON
(1 888 353 9426)
Tel: 1 610 814 2400
Fax: 1 610 814 0600
E-mail: sales@flexicon.com
Web: www.flexicon.com

CHILE

FLEXICON CHILE LIMITADA
Avenida Andres Bello # 1051
Oficina # 1602
Providencia
SANTIAGO
CHILE
Tel: +56 2 2415 1286
Fax: +56 2 2415 1393
E-mail: ventas@flexicon.com
Web: www.flexicon.com

UK

FLEXICON EUROPE Ltd.
182 John Wilson Business Park
Harvey Drive
Whitstable
Kent CT5 3RB
UNITED KINGDOM
Tel: +44 (0)1227 374710
Fax: +44 (0)1227 365821
E-mail: sales@flexicon.co.uk
Web: www.flexicon.co.uk

AUSTRALIA (BRISBANE)

FLEXICON CORPORATION
(AUSTRALIA) PTY LIMITED
78 Westgate Street
Wacol, QLD 4076
AUSTRALIA
Tel: +61 (0)7 3879 4180
Fax: +61 (0)7 3879 4183
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

AUSTRALIA (SYDNEY)

FLEXICON CORPORATION
(AUSTRALIA) PTY LIMITED
Suite 5, Level 3
45-47 Hunter St.
Hornsby, NSW 2077
AUSTRALIA
Tel: +61 (0)7 3879 4180
Fax: +61 (0)2 9477 5548
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

SOUTH AFRICA

FLEXICON AFRICA (PTY) LTD.
PO Box 10450
Linton Grange
Port Elizabeth 6015
SOUTH AFRICA
Tel: +27 (0)41 453 1871
Fax: +27 (0)41 453 1670
E-mail: sales@flexicon.co.za
Web: www.flexicon.co.za

flexicon®

BEV-CON™ Flexible Screw Conveyor for difficult-to-handle bulk materials

Conveys bulk solid materials that tend to pack, cake, smear, seize or break apart

Flexicon's BEV-CON™ conveyor handles powder and bulk solid materials that tend to pack, cake, smear, seize or break apart in general purpose conveyors. The unit transports difficult-to-convey solids from large pellets to sub-micron powders such as: pigments, titanium dioxide, fragile particles and products containing moisture, oil, fat and other additives that can cause materials to cake under slight pressure or frictional heat.

The enclosed conveyor tube prevents product and plant contamination, and enables products to maintain moisture and temperature levels, while the gentle rolling action of the inner spiral prevents the separation of blends. The rugged inner screw is the only moving part contacting material, resulting in reduced maintenance and increased reliability.

BEV-CON™ conveyors are available for low- to high-capacity applications in stationary configurations (shown) and as mobile units, designed, constructed and finished to industrial, food, (3-A) dairy and pharmaceutical standards.



BEV-CON™ conveyors can transport pigments, fragile particles, and moist, oily products that pack or cake under slight pressure or frictional heat.