

PRODUCT CONFIGURATIONS



U-1084

Hydraulic Bulk Bag Conditioner



USA

FLEXICON CORPORATION
2400 Emrick Boulevard
Bethlehem, PA 18020-8006
USA
Tel: 1 888 FLEXICON
(1 888 353 9426)
Tel: 1 610 814 2400
Fax: 1 610 814 0600
E-mail: sales@flexicon.com
Web: www.flexicon.com

UK

FLEXICON (EUROPE) LTD
182 John Wilson
Business Park
Harvey Drive
Whitstable, Kent CT5 3RB
United Kingdom
Tel: +44 (0)1227 374710
Fax: +44 (0)1227 365821
E-mail: sales@flexicon.co.uk
Web: www.flexicon.co.uk

SPAIN

FLEXICON (EUROPE) LTD
Sicilia 253, 4º, 1ª
08025 Barcelona
Spain
Tel: +34 647 670 302
E-mail: ventas@flexicon.es
Web: www.flexicon.es

SOUTH AFRICA

FLEXICON AFRICA (PTY) LTD
P.O. Box 10450
Linton Grange
Port Elizabeth 6015
South Africa
Tel: +27 41 453 1871
Fax: +27 41 453 1670
E-mail: sales@flexicon.co.za
Web: www.flexicon.co.za

CHILE

FLEXICON CHILE LTD
Avenida Andres Bello #1051
Oficina #1602
Providencia
Santiago
Chile
Tel: +56 2 2415 1286
Fax: +56 2 2415 1393
E-mail: ventas@flexicon.com
Web: www.flexicon.com

AUSTRALIA (SYDNEY)

FLEXICON CORPORATION
(AUSTRALIA) PTY LTD
Suite 5, Level 3
45-47 Hunter St.
Hornsby, NSW 2077
Australia
Tel: +61 (0)7 3879 4180
Fax: +61 (0)2 9477 5548
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

AUSTRALIA (BRISBANE)

FLEXICON CORPORATION
(AUSTRALIA) PTY LTD
78 Westgate Street
Wacol, QLD 4076
Australia
Tel: +61 (0)7 3879 4180
Fax: +61 (0)7 3879 4183
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

SINGAPORE

FLEXICON SINGAPORE PTE
LTD
27 West Coast Highway
#02-22
Singapore 117867
Tel: +65 6778 9225
Fax: +65 6690 8850
E-mail: sales@flexicon.com.sg

flexicon®

Hydraulic Bulk Bag Conditioner

This Hydraulic Bulk Bag Conditioner from Flexicon Corporation loosens bulk solid materials that have solidified during storage and shipment, enabling bulk bag unloaders to discharge the material through bag spouts.

The conditioner features two hydraulic rams with specially contoured end plates to press opposing sides of bulk bags. An optional hydraulically-actuated, variable-height turntable allows in-frame bag rotation, and conditioning of bulk bags at varying heights.

The number and pressure of hydraulic ram actuations, the height of the turntable, and the degree of rotation are user adjustable. The system controller and hydraulic pump can be mounted on the exterior of the safety cage or remotely. The conditioner is fully enclosed on all four sides for operator safety and includes full-height doors that are interlocked to disallow operation of the system when the doors are open.

The conditioner is intended for bulk bags containing hygroscopic chemicals, certain types of spice blends, heat-sensitive products, and other materials prone to solidifying to the point at which pneumatically-actuated flow promotion accessories integral to bulk bag dischargers are inefficient or completely ineffective.

Available as a stand alone unit or integral component of a bulk bag discharger, the unit measures 87" (2210 mm) H X 133" (3378 mm) W X 78" (1981 mm) D, accommodates bulk bags of all popular sizes, and requires only an electrical power connection for operation.



Flexicon's Hydraulic Bulk Bag Conditioner loosens bulk solid materials that have solidified during storage and shipment. (guards removed to show hydraulic cylinders)



The combined action of a hydraulically- actuated, variable-height turntable, and two hydraulic rams with specially contoured conditioning plates, presses opposing sides of bulk bags at varying heights to loosen compacted materials.