

PRODUCT CONFIGURATIONS



MOBILE

Low Incline BEV-CON™ Flexible Screw Conveyor



USA

FLEXICON CORPORATION
2400 Emrick Boulevard
Bethlehem, PA 18020-8006
USA
Tel: 1 610 814 2400
Fax: 1 610 814 0600
E-mail: sales@flexicon.com
Web: www.flexicon.com

CHILE

FLEXICON CHILE LTD
Avenida Andres Bello #1051
Oficina #1602
Providencia
Santiago
Chile
Tel: +56 2 2415 1286
Fax: +56 2 2415 1393
E-mail: ventas@flexicon.com
Web: www.flexicon.com

UK

FLEXICON (EUROPE) LTD
182 John Wilson Business Park
Harvey Drive
Whitstable
Kent, CT5 3RB
UK
Tel: +44 (0)1227 374710
Fax: +44 (0)1227 365821
E-mail: sales@flexicon.co.uk
Web: www.flexicon.co.uk

AUSTRALIA (BRISBANE)

FLEXICON CORPORATION
(AUSTRALIA) PTY LTD
78 Westgate Street
Wacol, QLD 4076
Australia
Tel: 1 300 FLEXICON
(1 300 3539426)
Tel: +61 (0)7 3879 4180
Fax: +61 (0)7 3879 4183
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

AUSTRALIA (SYDNEY)

FLEXICON CORPORATION
(AUSTRALIA) PTY LTD
Suite 5, Level 3
45-47 Hunter St.
Hornsby, NSW 2077
Australia
Tel: 1 300 FLEXICON
(1 300 3539426)
Tel: +61 (0)7 3879 4180
Fax: +61 (0)2 9477 5548
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

SOUTH AFRICA

FLEXICON AFRICA (PTY) LTD
PO Box 10450
Linton Grange
Port Elizabeth 6015
South Africa
Tel: +27 (0)41 453 1871
Fax: +27 (0)41 453 1670
E-mail: sales@flexicon.co.za
Web: www.flexicon.co.za

flexicon®

Low Incline BEV-CON™ Flexible Screw Conveyor

Versatile configurations conform to your application

This custom BEV-CON™ low-incline, mobile conveyor allows dust-free connections to both upstream and downstream equipment. It meets 3-A Dairy standards and is engineered to handle bulk solid products that tend to pack, cake or seize in general purpose conveyors.

The enclosed conveyor tube prevents product and plant contamination, and enables products to maintain moisture and temperature levels, while the gentle rolling action of the flexible screw prevents the separation of blends. The screw is the only moving part contacting material, resulting in reduced maintenance and increased reliability.

BEV-CON™ conveyors are characterized by straight conveyor tubes and can transport non-free-flowing as well as free-flowing materials horizontally, vertically or at any angle. All are offered in stationary and mobile configurations to satisfy low- to high-capacity requirements, and are available designed, constructed and finished to industrial, food, 3-A Dairy and pharmaceutical standards.

