

PRODUCT CONFIGURATIONS



J-0201

Manual Dumping Station for Flexible Screw Conveyors



USA

FLEXICON CORPORATION
2400 Emrick Boulevard
Bethlehem, PA 18020-8006
USA
Tel: 1 888 FLEXICON
(1 888 353 9426)
Tel: 1 610 814 2400
Fax: 1 610 814 0600
E-mail: sales@flexicon.com
Web: www.flexicon.com

CHILE

FLEXICON CHILE LIMITADA
Avenida Andres Bello # 1051
Oficina # 1602
Providencia
SANTIAGO
CHILE
Tel: +56 2 2415 1286
Fax: +56 2 2415 1393
E-mail: ventas@flexicon.com
Web: www.flexicon.com

UK

FLEXICON EUROPE Ltd.
182 John Wilson Business Park
Harvey Drive
Whitstable
Kent CT5 3RB
UNITED KINGDOM
Tel: +44 (0)1227 374710
Fax: +44 (0)1227 365821
E-mail: sales@flexicon.co.uk
Web: www.flexicon.co.uk

AUSTRALIA (BRISBANE)

FLEXICON CORPORATION
(AUSTRALIA) PTY LIMITED
78 Westgate Street
Wacol, QLD 4076
AUSTRALIA
Tel: +61 (0)7 3879 4180
Fax: +61 (0)7 3879 4183
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

AUSTRALIA (SYDNEY)

FLEXICON CORPORATION
(AUSTRALIA) PTY LIMITED
Suite 5, Level 3
45-47 Hunter St.
Hornsby, NSW 2077
AUSTRALIA
Tel: +61 (0)7 3879 4180
Fax: +61 (0)2 9477 5548
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

SOUTH AFRICA

FLEXICON AFRICA (PTY) LTD.
PO Box 10450
Linton Grange
Port Elizabeth 6015
SOUTH AFRICA
Tel: +27 (0)41 453 1871
Fax: +27 (0)41 453 1670
E-mail: sales@flexicon.co.za
Web: www.flexicon.co.za

flexicon®

Manual Dumping Station for Flexible Screw Conveyors

Collects dust created during manual dumping operations

Flexicon's Manual Dumping Station with integral flexible screw conveyor collects dust created during manual dumping of powder and bulk solid materials from bags, boxes, drums and other containers. The unit is intended to reduce material waste and eliminate the need to clean a remote dust collection site, while protecting workers and preventing plant contamination.

It features a high velocity vacuum fan that draws airborne dust from the operator's atmosphere onto two cartridge filters. Automatic reverse-pulse filter cleaning allows continuous, efficient operation; timer activated solenoid valves release short blasts of compressed plant air inside cartridge filters causing dust build-up on the outer filter surfaces to fall into the hopper.

Filters are accessed easily by removing the interior baffle, and replaced rapidly using quick-disconnect fittings.

The flexible screw conveyor handles free- and non-free-flowing bulk materials ranging from large pellets to sub-micron powders, including products that pack, cake, seize, smear, fluidize, break-apart or separate.

The system is available mounted on frames with boom and casters for in-plant mobility, and is constructed of carbon steel with durable industrial finish, or stainless steel finished to industrial, food, dairy or pharmaceutical standards.

Hoppers are also available configured for connection to pneumatic conveyors or process equipment.



Filters are accessed easily by removing the interior baffle, and replaced rapidly using quick-disconnect fittings.



Timer activated solenoid valves release short blasts of air inside cartridge filters causing dust build-up to fall into the hopper. The hopper shown is configured for direct connection to a flexible screw conveyor. Other configurations allow connection to pneumatic conveyors or other conveyors and process equipment.