

PRODUCT CONFIGURATIONS



V-1064

Pivot-Head Filler Accommodates Bulk Bags, Drums



USA

FLEXICON CORPORATION
2400 Emrick Boulevard
Bethlehem, PA 18020-8006
USA
Tel: 1 610 814 2400
Fax: 1 610 814 0600
E-mail: sales@flexicon.com
Web: www.flexicon.com

CHILE

FLEXICON CHILE LTD
Avenida Andres Bello #1051
Oficina #1602
Providencia
Santiago
Chile
Tel: +56 2 2415 1286
Fax: +56 2 2415 1393
E-mail: ventas@flexicon.com
Web: www.flexicon.com

UK

FLEXICON (EUROPE) LTD
182 John Wilson Business Park
Harvey Drive
Whitstable
Kent, CT5 3RB
UK
Tel: +44 (0)1227 374710
Fax: +44 (0)1227 365821
E-mail: sales@flexicon.co.uk
Web: www.flexicon.co.uk

SINGAPORE

FLEXICON SINGAPORE PTE LTD
27 West Coast Highway
#02-22 Singapore 117867
Tel: +65 6778 9225
Fax: +65 6690 8850
E-mail: sales@flexicon.com.sg
Web: www.flexicon.com.sg

AUSTRALIA (BRISBANE)

FLEXICON CORPORATION
(AUSTRALIA) PTY LTD
78 Westgate Street
Wacol, QLD 4076
Australia
Tel: 1 300 FLEXICON
(1 300 3539426)
Tel: +61 (0)7 3879 4180
Fax: +61 (0)7 3879 4183
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

AUSTRALIA (SYDNEY)

FLEXICON CORPORATION
(AUSTRALIA) PTY LTD
Suite 5, Level 3
45-47 Hunter St.
Hornsby, NSW 2077
Australia
Tel: 1 300 FLEXICON
(1 300 3539426)
Tel: +61 (0)7 3879 4180
Fax: +61 (0)2 9477 5548
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

SOUTH AFRICA

FLEXICON AFRICA (PTY) LTD
PO Box 10450
Linton Grange
Port Elizabeth 6015
South Africa
Tel: +27 (0)41 453 1871
Fax: +27 (0)41 453 1670
E-mail: sales@flexicon.co.za
Web: www.flexicon.co.za

flexicon[®]

Pivot-Head Filler Accommodates Bulk Bags, Drums

Flexicon's combination bulk bag/drum filler features a fill head that pivots down for connecting empty bags at floor level, and a swing-arm-mounted chute for filling of drums.

The unit's SWING-DOWN® fill head enables the operator to connect bag spouts and resume filling operations rapidly, eliminating the need to step over roller conveyors, strain to reach overhead connection points, or risk injury associated with operation of conventional bulk bag fillers.

The patented device simultaneously lowers and pivots the fill head, stopping it in a vertically oriented position that places the bag inlet spout inflatable connection, inflator button, and four bag loop latches within an arm's length of an operator standing on the plant floor. This increases the safety and speed of connecting bulk bags, since the connection points of a conventional filler are beyond the reach of most operators, even when bags as short as 4 ft (1220 mm) in height are being filled.

A remote console or wall-mounted panel houses controls to raise and pivot the fill head into a locked, horizontal "fill position," automatically inflate the bag to remove creases, open a flow control valve or start a feed device, and stop the flow of material once a preset fill weight has been gained. Optional vibratory decks de-aerate and densify material in the bag at preset set points to create a solid, stable bag, ready for shipment.

Once bags are filled, the controller deflates the spout connection collar, releases the loop latches, and raises the fill head to fully disengage the spout, enabling the bag to exit the filler automatically on the roller conveyor.

The unit can be switched to drum filling mode in several seconds by positioning the swing-arm-mounted drum-filling chute under the fill head discharge port. The chute automatically rotates to deliver material to all four drums on a pallet.

The filler is constructed of carbon steel with durable industrial finish, or stainless steel finished to industrial, food, dairy or pharmaceutical standards, and is offered with material delivery systems integrated with upstream process equipment or other material source.



Combination bulk bag/drum filler features a fill head that pivots down to allow safe, rapid bag spout connections, and a swing-arm-mounted drum filling chute that automatically rotates to fill four drums on a pallet.