



EGS-750 *Entraguard Silver* Telephone Entry System

Standard Features for Telephone Entry

- Stand alone functionality or seamless integration with Keri's access control system and *Doors*™ software for real access control and telephone entry integration
- Four line, large font, soft white supertwist LCD display, Lexan™ cover
- Three 80 character, programmable, scrolling pages for instructions and messages with automatic timed rotation
- 750 tenant capacity, customer does not pay for extra capacity
- Up to 6-digit directory code, up to 5-digit Entraguard ID codes (PINs), up to 15-digit telephone numbers
- Networkable to manage multiple doors via RS-485
- Time Zone restrictions for calling tenants and for PINs
- Links a visitor to the resident who allowed entry
- Telephone entry units and access control units can be combined on a single network for a total of 128 controller units
- Flexible connectivity: RS-232, Modem, TCP/IP
- Stores up to 3,640 events, manages up to 255 individual sites
- Weather and vandal resistant housing
- Programmable talk time, tone dialing, adjustable volume
- Quick disconnect terminals
- Two Mylar™ speakers with superior sound
- Heavy duty door and alarm relays, door forced open and door held open alarms
- Built-in surge protection, non volatile memory
- Powerful *Doors*™ Access Control Software with full access control features: time zones, temporary users, online programming, operator security levels, multiple site management, and automatic configuration



EGS-750

The *Entraguard Silver* is the mid size offering in Keri's telephone entry product line. With a large-font, 4-line, scrolling display, the *Silver* has a 750 tenant capacity, enough to handle the large majority of projects. Designed for looks and durability, it comes in an attractive, weather resistant, 14-gauge brushed stainless steel enclosure. The *Silver* entry panel is available at a price well below competitive medium capacity systems on the market. A no-phone-line system is available as an option.

Like its sister products, the *Entraguard Platinum* and *Titanium*, the *Silver* provides the best telephone entry/access control marriage by letting the unit function as a node on a *PXL* controller network, putting both applications under the acclaimed *Doors*™ software umbrella for a seamless integration of the two. Additionally, the *Silver*, like the *Platinum*, can contain a *PXL-500 Tiger Controller* and an *SB-593 Satellite Expansion Board* for up to two doors of built-in card access in the same housing. A walk-up package addresses the basic visitor and resident control for the main entrance to a building.

Each *Entraguard Silver* also has two extra relay outputs that can be used in a variety of ways including turning on a lobby light, unlocking an interior door, or providing access to two separate entrances by using tone commands from the tenant's location or based on an access granted decision. An on-board modem is also included for remote programming.

Entraguard™

EGS-750 *Entraguard Silver*




2305 Bering Drive • San Jose, California • 95131
408-435-8400 • Toll Free: 800-260-5265 • Fax: 408-577-1792

e-mail: sales@kerisys.com • web: www.kerisys.com

EGS-750 Entraguard Silver Telephone Entry System

Access Control Features

- True, integrated access control with **PXL-500 P or W** controllers - the **Silver** becomes part of a Keri access control network
- Simple, one button auto-configuration
- 32 time zones, 3 holiday schedules
- Unlimited access control groups
- Automatically expiring **Entraguard** IDs (PINs) and cards
- Time Zones on **Entraguard** IDs (PINs) and cards, as well as doors and gates
- Full reporting of events
- Direct door operation from PC
- Automatic lock and unlock of doors and gates
- Assignable inputs and outputs (when using an optional **SB-593** on a **PXL-500**)
- Rollcall/track, muster
- Image capture and optional badge printing
- Remote online management of multiple sites
- System operator security levels with configurable privileges



Special Telephone Entry Features

- Do not Disturb Call Feature - programmable for individual tenants
- Do not Display Name Feature - programmable on a per tenant basis
- Remote online management of multiple sites
- Ability to link visitors to the residents who allowed them entry
- Ability to update several units in one pass
- Pre-wired walk-up package

When using *Entraguard* products in a dial-up application, Keri requires the use of an approved modem. Please refer to the Recommended Peripherals list on the web site or contact Keri customer service.

General Features:

- Surface or recess mount
- Weather and vandal resistant housing
- Postal lock provision
- Non-volatile memory
- Built-in surge protection plus surge protection kit
- Programmable talk time
- Door forced open and door held open alarms
- Tone dialing
- Alarm output relay
- Adjustable volume control
- Maintenance free LED lighting
- Two Mylar™ speakers with superior sound
- Quick disconnect terminals

Specifications*:

- Capacity: Up to 750 Tenants
- Outputs: Door Relay, Alarm Relay, 2 additional programmable relays
- Operating Temperature: +5° to 140° F (-15° to 60° C) with heater: -20° to 140° F (-29° to 60° C)
- Input Power: 12 VDC @ 1 A
- Current Draw: 750 mA
- Relay Contact Rating: 1 A @ 24 VDC
- Size: 13.88" H x 10.34" W x 3.5" D (35.3 cm x 26.3 cm x 8.9 cm)
- Weight: 12.30 lbs (6.09 kg)
- Material: 14 gauge stainless steel
- Warranty: 2 years
- Finish: Brushed Stainless Steel

Options / Accessories:

- Camera
- Postal Lock
- Handset
- Hooded Enclosure / Pedestal Mount
- Recessed Wall Mount Kit
- Heater (for operation below 5° F/-15° C)
- No Phone Line System

* Specifications subject to change without notice.

All trademarks are the property of their respective owners.

Presented By:



P/N: 01751-002