

Warm air hand dryers

Topflow



6 YEAR GUARANTEE

Operation: Push button with timer
 Dimensions: 287 x 244 x 206 mm.
 Weight: 8,16 kg.
 Total power: 2300 W
 Anti-vandalism structure



Drying in 12-15 seconds
 Saving: 50% of electricity



MTS

Casing: AISI 304 Stainless steel
 Casing Finish: Satin



MTB

Casing: Stamped steel
 Casing Finish: White



MTC

Casing: AISI 304 Stainless steel
 Casing Finish: Polished



MTF

Casing: Cast Iron
 Casing Finish: White
 Weight: 13,15 kg.

Topflow

Operation: Electronic sensor



MTSA

Casing: AISI 304 Stainless steel
 Casing Finish: Satin



MTBA

Casing: Stamped steel
 Casing Finish: White



MTCA

Casing: AISI 304 Stainless steel
 Casing Finish: Polished



MTFA

Casing: Cast Iron
 Casing Finish: White
 Weight: 13,15 kg.

Topflow

Operation: Electronic sensor / Push button
 Dimensions: 333 x 351 x 102 mm.

RECESSED



MTSA-E

Casing: AISI 304 Stainless steel
 Casing Finish: Satin
 Weight: 12,0 kg.



MTFA-E

Casing: Cast Iron
 Casing Finish: White
 Weight: 15,88 kg.



MTF-E

Casing: Cast Iron
 Casing Finish: White
 Weight: 15,88 kg.

Warm air hand dryers
Technical features
Topflow



Technical features	TOPFLOW
Voltage / Frequency	220 – 240 V 50/60 Hz.
Total power	2.300 W
Power resistance	1.600 W
Motor power	700 W
Type	Universal with brushes
r.p.m	12.000
Sound level at 2m.	73,8 dB
Airflow	6.740 l/min (404 m ³ /h)
Airspeed	157 km/h
Temperature at 10 cm. (room temperature approx. 21°C)	49°
Drying time	15 s.
Electrical insulation	Class I
Protection rating against water projections	IP23
Timer control in push-button models	20 s.
Standards	CE, TÜV-GS