





Jofra Dry Block Calibrators

Unique technology offering optimum dry-block perfomance

- 12 models temperature ranges -90 to +650°C
- Accuracy/Stability ±0.4°C / ±0.01°C
- · Models for Liquid, or
- RS232, and Jofracal Software
- External Sensor
- Interchangeable Multihole Inserts



TBS1 Temperature Calibration Bath

Easy calibration checks on food-use thermometers and probes.

- Temperature range: 0°C to +50°C
- Accuracy: ±0.2% ±0.1 of reading



CALIBRATION EQUIPMENT & SERVICES

AMETEK®

JOFRATM



Temperature:

- Dry Block Calibrators
- Water Baths
- Process Calibrators for thermocouples, rtd's, mV, and mA

Current/Voltage:

- mA Loop Calibrators
- mV and mA Calibration

Pressure:

- Precision Calibrators
- Portable Pressure Calibrators
- Multi-function Hand Pump

Service/Calibration

- Repair/ Calibration of instruments and temperature probes.
- UKAS Calibration Certificates
- In- house calibration against UKAS calibrated equipment



Jofra Reference Digital Temperature Indicator and Sensors

A highly accurate and traceable thermometer for reference applications.

- Temperature range -200 to 750°C
- Digital accuracy to ±0.004°C
- RS232 interface and JOFRACAL software
- Dual channel inputs
- Accepts Pt100/PT25 Rtd's





DS1M-T Calibrator

Easy electronic calibration of digital thermometers with T or K thermocouple inputs. Preset calibration points

MicroCal 20 DPC Calibrator

Rugged, hand-held, multifunction calibrator for most process parameters

> A206 0709

Tempcon Instrumentation Ltd.
Unit 19, Ford Lane Business Park, Ford Lane
Ford, Nr. Arundel, West Sussex. BN18 0UZ
Tel: +44 (0) 1243 558270 Fax: +44 (0) 1243 558288
Email: info@tempcon.co.uk Web site: www.tempcon.co.uk