

P30 Stripping Machine



The Stripper P 30 / ...

are used in the cable pre-assembling industry ,when cables, ready for further processes are requested. The machines work semi-automatic and are suitable for mass production whenever the outer jacket of the cable has to be removed.

The machines are very compact and easy to use.

Function:

The cable beginning is placed into the stripper till the set end stop is reached. Then the foot interrupter is activated. In one step, with help of an installed pneumatic system, the outer jacket is cut and stripped of. The stripped cable can be pulled out. The stripped off jacket falls through a shaft under the machine into a collection tank.

It is very easy to change the stripper blade and cable guide tubes for the suitable stripping length without any tools.

Stripping blades, guide tubes and press blocks are not included in the basic equipment

Cable diameter	max. 30 mm (optionally up to 34 mm)
Stripping lengths (Full withdrawal) Type of machine	continuously adjusted by scaling - P 30/50 to 50 mm - P 30/100 to 100 mm - P 30/300 up to 300 mm - P 30/500 up to 500 mm - P 30/1000 to 1000 mm - P 30/1500 up to 1,500 mm
Operation	by foot switch or sensor
Compressed air connection	6 - 8 bar
Dimensions depending on the type	750-4300 x 500 x 410 mm
Weight	about 25 - 120 kg