

Security Packaging Tape - SK88

PET labelstock material for security labels. Upon removal an irreversible void message appears in the label itself. No adhesive residue remains on the surface underneath. It has an acrylic adhesive system and is available in a range of colours.

APPLICATION

Suitable for manufacture of security labels used for sealing access doors, reusable packaging like crates, trolleys, containers and aircraft doors. Indoor and outdoor applications, weatherproof.

The material is suitable for most common printing methods including thermal transfer, flexographic and digital (primer may be required). Various additional security features can be added to the labels for personalisation and security enhancement.

APPLICATION CONDITIONS

18 - 25°C (R.H. 55% ±5%)

PHYSICAL PROPERTIES

Technical Descriptions	
Presentation	Labels stock master reel / slit rolls / plain or printed labels
Adhesive	Acrylic resin, pressure sensitive
Backing	PET, 40 Micron
Total Thickness	0.11 Micron

TECHNICAL PROPERTIES

Technical Descriptions	Value	Unit	Test Method
Temperature Resistance	0-80	°C	
Initial Tack	<10	cm	PSTC-6 #14 ball
Holding Power (1.0kg/25mm ²)	>72	Hours	PSTC-7
Peel Adhesion to Steel	>9.8	N/25mm	PSTC-1

ADDITIONAL INFORMATION

Last two digits in the product code represent the tape colour. Standard colours are:
00 black, **01** blue, **02** red, **03** green, **04** yellow, **05** grey, **06** purple, **08** white, **10** orange

APPLICATION RECOMMENDATIONS

For best results apply with pressure at room temperature on a clean surface, free of dust and grease and allow a minimum of 1 minute for achieving optimal bond strength.

All statements, technical information and recommendations are based on tests we believe to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose. Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller nor Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.