

Security Packaging Tape - SK77

Pressure-sensitive tamper-evident packaging tape. Reveals an obvious void message on removal. SK77 has a strong PET backing and acrylic adhesive system with good temperature resistance. The permanent total transfer void message remains on the surface with a trace performance of 95% minimum. This secure packaging tape is used for valuable goods in storage and transit, particularly applications where security and appearance are important.

APPLICATION

Suitable for sealing cartons and boxes, plain or laminated cardboard and plastics. Also, for pallet wrapping films to secure pallets in transit and air cargo.

Standard roll sizes can be used in hand dispensers for packaging tape with a sharp blade. For machine application long length rolls are available up to 500m.

TECHNICAL PROPERTIES

| Technical Descriptions | |
|------------------------|---|
| Presentation | Self-wound, 3-inch core |
| Roll Size | 50mm x 50m (40mm, 50mm, 75mm x 50 - 500m) |
| Adhesive | Acrylic solvent, pressure sensitive |
| Backing | PET, 25 Micron |
| Total Thickness | 80 Micron |
| Standard Colours | Blue (SK7701), Red (SK7702), Brown (SK7717) |
| Additional Features | Perforations, sequential numbering, bespoke void message, top print |

TECHNICAL PROPERTIES

| Technical Descriptions | Value | Unit | Test Method |
|--|-----------|----------------|-----------------|
| Temperature Resistance | -40 - +80 | °C | |
| Initial Tack | <10 | cm | PSTC-6 #14 ball |
| Holding Power (1.0kg/25mm ²) | >24 | Hours | PSTC-7 |
| 90° Peel Adhesion for Void | 20 - 100 | Grams per 25mm | |

ADDITIONAL INFORMATION

Last two digits in the product code represent the tape colour. Standard colours are:

00 black, **01** blue, **02** red, **03** green, **04** yellow, **05** grey, **06** purple, **08** white, **10** orange, **17** havana brown

APPLICATION RECOMMENDATIONS

For best results apply with pressure at room temperature on a clean surface, free of dust and grease and allow a minimum of 1 minute for achieving optimal bond strength.

All statements, technical information and recommendations are based on tests we believe to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose. Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller nor Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.