

DIODE PID

Electronically regulated welding temperature for perfect working. Its external air supply makes it suitable for mobile installation work.

- Temperature electronically regulated and digitally displayed
- Electronic heating element protection
- Adaptor tube with heat protection
- Push-fit and screw-on nozzles for round and profile welding rods
- Air supply provided by the ROBUST or MINOR blowers
- Suitable for mobile assembling applications when connected to the MINOR blower



SPECIFICATIONS

DIODE PID 42 V

Voltage	V~	42
Power consumption	W	600
Frequency	Hz	50 / 60
Temperature	°C	20 – 600
Min. Air flow (20° C)	l/min	40
Pressure dynamic	Pa	max. 10 ⁵ (1000 mbar)
Size (L x ø)	mm	265 x 57, handle Ø 40
Weight	kg	1.15 (with 3 m cord / 3 m air hose)

Marking of conformity



Approval mark



Certification scheme

CCA




Protection class II






DIODE PID 100 V

Voltage	V~	100
---------	----	-----

Plastic Welding > Hand tools > DIODE PID

Power consumption	W	1400
Frequency	Hz	50 / 60
Temperature	°C	20 – 600
Min. Air flow (20° C)	l/min	40
Pressure dynamic	Pa	max. 10 ⁵ (1000 mbar)
Size (L x ø)	mm	265 x 57, handle Ø 40
Weight	kg	1.15 (with 3 m cord / 3 m air hose)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		




DIODE PID 120 V

Voltage	V~	120
Power consumption	W	1600
Frequency	Hz	50 / 60
Temperature	°C	20 – 600
Min. Air flow (20° C)	l/min	40
Pressure dynamic	Pa	max. 10 ⁵ (1000 mbar)
Size (L x ø)	mm	265 x 57, handle Ø 40
Weight	kg	1.15 (with 3 m cord / 3 m air hose)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		

DIODE PID 230 V

Voltage	V~	230
---------	----	-----

Plastic Welding > Hand tools > DIODE PID

Power consumption	W	1600
Frequency	Hz	50 / 60
Temperature	°C	20 – 600
Min. Air flow (20° C)	l/min	40
Pressure dynamic	Pa	max. 10 ⁵ (1000 mbar)
Size (L x ø)	mm	57 x 265, handle Ø 40
Weight	kg	1.15 (with 3 m cord / 3 m air hose)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		



Plastic Welding > Hand tools > DIODE PID

ACCESSORIES