

ELECTRON

The most powerful hand tool from Leister. Compact, robust and construction site tried and tested.

- Powerful
- Compact
- Robust
- Construction site tried and tested



SPECIFICATIONS

ELECTRON 42 V

Voltage	V~	42
Power consumption	W	1000
Frequency	Hz	50 / 60
Temperature	°C	20 – 650
Air flow (20°C)	l/min	320, manual air slide
Pressure static	Pa	3000 (30 mbar)
Noise emission level LpA	dB	65
Size (L x ø)	mm	320 x 95, handle Ø 64
Weight	kg	1.5 (with 3 m cord)

Marking of conformity



Approval mark



Certification scheme

CCA




Protection class II






ELECTRON 120 V

Voltage	V~	120
Power consumption	W	2700

Plastic Welding > Hand tools > ELECTRON

Frequency	Hz	50 / 60
Temperature	°C	20 – 650
Air flow (20°C)	l/min	320, manual air slide
Pressure static	Pa	3000 (30 mbar)
Noise emission level LpA	dB	65
Size (L x ø)	mm	320 x 95, handle Ø 64
Weight	kg	1.5 (with 3 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		




ELECTRON 200 V

Voltage	V~	200
Power consumption	W	3000
Frequency	Hz	50 / 60
Temperature	°C	20 – 650
Air flow (20°C)	l/min	320, manual air slide
Pressure static	Pa	3000 (30 mbar)
Noise emission level LpA	dB	65
Size (L x ø)	mm	320 x 95, handle Ø 64
Weight	kg	1.5 (with 3 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		




ELECTRON 230 V 2300

Voltage	V~	230
---------	----	-----

Plastic Welding > Hand tools > ELECTRON

Power consumption	W	2300
Frequency	Hz	50 / 60
Temperature	°C	20 – 650
Air flow (20°C)	l/min	320, manual air slide
Pressure static	Pa	3000 (30 mbar)
Noise emission level LpA	dB	65
Size (L x ø)	mm	320 x 95, handle Ø 64
Weight	kg	1.5 (with 3 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		

ELECTRON 230 V 3400

Voltage	V~	230
Power consumption	W	3400
Frequency	Hz	50 / 60
Temperature	°C	20 – 650
Air flow (20°C)	l/min	320, manual air slide
Pressure static	Pa	3000 (30 mbar)
Noise emission level LpA	dB	65
Size (L x ø)	mm	320 x 95, handle Ø 64
Weight	kg	1.5 (with 3 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		





ACCESSORIES