

## MINOR




Powerful blower for DIODE PID and DIODE S.

- Lightweight and compact
- Powerful
- Mobile air supply for Leister welding machines



## SPECIFICATIONS




### MINOR 42 V

Voltage	V~	42
Power consumption	W	100
Frequency	Hz	50 / 60
Air flow (20°C)	l/min	400
Pressure static	Pa	4000
Noise emission level LpA	dB	67
Outlet opening (outside)	mm	14.5
Size (L x Ø)	mm	250 x 95, handle Ø 64
Weight	kg	1.15 (with 3 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		




### MINOR 120 V

Voltage	V~	120
Power consumption	W	100
Frequency	Hz	50 / 60
Air flow (20°C)	l/min	400

## Plastic Welding &gt; Hand tools &gt; MINOR

Pressure static	Pa	4000
Noise emission level LpA	dB	67
Outlet opening (outside)	mm	14.5
Size (L x ø)	mm	250 x 95, handle Ø 64
Weight	kg	1.15 (with 3 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		

## MINOR 230 V

Voltage	V~	230
Power consumption	W	100
Frequency	Hz	50 / 60
Air flow (20°C)	l/min	400
Pressure static	Pa	4000
Noise emission level LpA	dB	67
Outlet opening (outside)	mm	14.5
Size (L x ø)	mm	250 x 95, handle Ø 64
Weight	kg	1.15 (with 3 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		



Plastic Welding > Hand tools > MINOR

---

## ACCESSORIES