

VARIMAT V


Hot-air welding machine for overlap welding of roofing membranes. With digital display or the set and actual values.

- Overlap welding of PVC-P, ECB, EPDM, CSPE and TPO roofing membranes as well as elastomer bitumen
- Easy welding, also of homogenous and thin roofing membranes
- Wrinkle-free welding up to 5 m/min
- Patented pendulum pressure roller guarantees uniform pressure also on uneven surfaces
- Digital display of set and actual values of welding speed and temperature
- Constant temperature and speed independent of voltage fluctuations and ambient temperature



SPECIFICATIONS

VARIMAT 230 V

Voltage	V~	230
Power consumption	W	4600
Frequency	Hz	50 / 60
Temperature	°C	20 - 620
Speed	m/min	0.5 - 5
Welding pressure	N	190
Air flow range	%	50 - 100
Pressure static	Pa	5000 (50 mbar)
Noise emission level LpA	dB	67
Welding seam width	mm	40
Size (L x W x H)	mm	640 x 430 x 330
Weight	kg	35.0 (with 5 m cord)
Marking of conformity		

Plastic Welding > Welding machines > VARIMAT V

Approval mark



Protection class I



VARIMAT 400 V

Voltage	V~	400
Power consumption	W	5700
Frequency	Hz	50 / 60
Temperature	°C	20 - 620
Speed	m/min	0.5 - 5
Welding pressure	N	190
Air flow range	%	50 - 100
Pressure static	Pa	5000 (50 mbar)
Noise emission level LpA	dB	67
Welding seam width	mm	40
Size (L x W x H)	mm	640 x 430 x 330
Weight	kg	35.0 (with 5 m cord)
Marking of conformity		
Approval mark		
Protection class I		



ACCESSORIES