



Suppliers, Importers & Exporters of **LEISURE & INDUSTRIAL NETTING, TWINE & ROPE**
 Pelham Industrial Estate, Manby Road, Immingham, DN40 2SE England
 Tel: (01469) 575804 e-mail: netting@renco.co.uk www.renco.co.uk

PRODUCT CERTIFICATION:

PRODUCT	2.5MM BRAIDED POLYETHYLENE NETTING
RAW MATERIAL	POLETHYLENE HIGH DENSITY
COLOURS	BLACK
COMPOSITION	16 X 2 = 32 MONOFILAMENTS PE
CORE	SPLIT FILM CORE
DIAMETER MONOFILAMENT PE	0.26MM = 510 DTEX
DIAMETER TWINE	2.5MM
RUNNAGE TWINE	430M/KG
BREAKING STRENGTH TWINE	82KG
ELONGATION AT BREAK	22%
HOT AIR 160° SHRINKAGE	15%
DENSITY	0.95GR / CM3.(FLOAT)
KNOT TO KNOT NETTING	25MM (56MM FULL MESH)
KNOT STRENGTH	63KG
WEIGHT SQUARE MESH	260GR / M2
PRESENTATION	TERMOFIXED

DATE	01.01.2019	
SIGNATURE MANAGER	<i>M. Hall</i>	