

## RonaGrip Instant Ladder Rung

Pre-formed GRP slip resistant instant ladder rung cover



### FEATURES

- highly slip resistant
- easy to apply
- can be trafficked instantly
- hard wearing and durable
- installed in virtually any environment
- corrosion resistant
- choice of sizes
- suitable for industrial, commercial and retail use
- cost efficient solution to ladder safety

### Description

RonaGrip Instant Ladder Rung is designed specifically to fit over traditional steel ladder rungs.

RonaGrip Instant Ladder Rung enhances ladder safety by enlarging the surface area for foot contact and friction coefficient with its integral grit surface.

Constructed from durable chemical resistant fibreglass, RonaGrip Instant Ladder Rung is capable of withstanding the busiest of environments and will resist chemical attack from corrosive fluids transferred from the sole of the boot

### Uses

- Internal and external use
- Suitable for industrial, commercial and retail use
- Emergency slip resistant solution

### Instructions for Use

#### Preparation

Prepare the surface and ensure that it is clean and free of any loose or friable material that can effect the adhesion. Using a suitable abradar, rub down the substrate to give a suitable key.

#### Installation

Turn the rung cover upside down and apply a 6mm bead (this may need to be increased depending on the size of the rung) of RonaGrip Instant Adhesive around the inside of the rung cover. Then simply push the RonaGrip Instant Ladder Rung over the rung and twist to ensure the adhesive coats the rung. Level the RonaGrip Instant Ladder Rung so that the top surface is completely horizontal. A spirit level can be used if required.

# RonaGrip Instant Ladder Rung

## Pre-formed GRP slip resistant instant ladder rung cover

### Packaging

RonaGrip Instant Ladder Run is available in 2 standard sizes. It is supplied in either 25mm x 25mm x 25mm or 38mm x 38mm x 38mm. The maximum length available is 1200mm. A free cutting service is available to meet project requirements. The standard stock colour is yellow.

A free cutting service is available to meet project requirements.

### Slip Resistance

Using the pendulum test method, the RonaGrip Instant Ladder Rung achieved a Slip Resistance Value of 65 in the dry and 60 in the wet classifying it as low risk of slip.

### Slip Resistance

Non-hazardous. Protective clothing such as goggles, overalls and gloves is recommended to prevent any effect from prolonged skin contact, inhalation or ingestion of RonaGrip Instant Adhesive MP10. Refer to Health and Safety Data Sheet.

### Technical Service and Support

Ronacrete provide free technical advice and support during design and installation of all systems for flooring, concrete repair, bonding, bedding and waterproofing. If you need any further information or a full technical data sheet contact the Ronacrete Technical Department on +44 (0) 1279 638 700.

### Site Attendance

When on site Ronacrete representatives are able, if asked, to give a general indication of the correct method of installing a Ronacrete product. It is important to bear in mind that Ronacrete Ltd is a manufacturer and not an application contractor and it is therefore the responsibility of the contractor and his employer to ensure he is aware of and implements the correct practices and procedures to ensure the correct installation of the product and that liability for its correct installation lies with the contractor and not with Ronacrete Ltd.

The information detailed in this leaflet is liable to modification from time to time in the light of experience and of normal product application, and before using, customers are advised to check with Ronacrete Ltd, quoting the reference number, that they possess the latest issue. Any person or company using the product without first making further enquiries as to the suitability of the product for the intended use does so at his own risk, and Ronacrete Ltd can accept no responsibility for the performance of the product, or for any loss or damage arising out of such use.