











RonaGrip Instant Stair Tread

Pre-formed GRP instant slip resistant stair tread



FEATURES

- cost efficient solution to ladder safety
- internal and external application
- suitable for industrial, commercial and retail use
- highly slip resistant
- easy to apply
- can be trafficked instantly
- hard wearing and durable
- installed in virtually any environment
- choice of size
- corrosion resistant

Description

RonaGrip Instant Stair Tread is a high quality composite of glass woven matting impregnated with polyester resin. The energy absorption and flexibility of RonaGrip Instant Stair Tread ensures its long life, even in the busiest of environments.

A compound of carbon and silicon grit is added in the final layer of the laminate providing a superb slip resistant and hard wearing surface.

RonaGrip Instant Stair Tread is resistant to a wide range of chemicals and is perfectly suited for use even in the harshest of environments.

The versatility of RonaGrip Instant Stair Tread allows it to be applied to almost any surface such as concrete, steel or wood. The fact that it is supplied as a finished product means that it can be walked on straight away thus keeping disruption to a minimum.

Instructions for Use

Preparation

Prepare the surface and ensure that it is clean and free of any loose or friable material that can effect the adhesion.

Adhesive

Apply the RonaGrip Instant Adhesive MP10 onto the back of the tread.

Installation

Carefully place the RonaGrip Instant Stair Tread onto the edge of the stair. Once in place drill two holes on each side of the tread cover, one approximately 15mm in from the back edge and 15mm from the side. The second one should again be approximately 15mm from the side and approximately 10mm back from the contrasting nosing (55mm). For larger treads, it may be necessary to have further fixing points in the centre of the tread.

RonaGrip Instant Stair Tread

Pre-formed GRP instant slip resistant stair tread

Slip Resistance

Using the pendulum test method, RonaGrip Instant Stair Tread achieved a Slip Resistance Value of 105 in the dry (Extremely low risk) and 67 in the wet (extremely low risk).

Packaging

RonaGrip Instant Stair Tread are available in a maximum 3000mm wide x 345mm deep with a 55mm yellow nosing incorporated into the tread and 55mm down the riser.

The product is nominally 4mm thick with the nosing set at 85 °.

A cutting service is available to cut the RonaGrip Instant Stair Tread to your desired size on both the length and the depth.

RonaGrip Instant Stair Tread is supplied as standard in 3 colours.

- Black with Yellow Nosing
- Black with White Nosing
- All stone

Health and Safety

Non-hazardous. Protective clothing such as goggles, overalls and gloves is recommended to prevent any effect from prolonged skin contact, inhalation or ingestion of RonaGrip Instant Adhesive MP10. Refer to Health and Safety Data Sheet.

Site Attendance

When on site Ronacrete representatives are able, if asked, to give a general indication of the correct method of installing a Ronacrete product. It is important to bear in mind that Ronacrete Ltd is a manufacturer and not an application contractor and it is therefore the responsibility of the contractor and his employer to ensure he is aware of and implements the correct practices and procedures to ensure the correct installation of the product and that liability for its correct installation lies with the contractor and not with Ronacrete Ltd.

The information detailed in this leaflet is liable to modification from time to time in the light of experience and of normal product application, and before using, customers are advised to check with Ronacrete Ltd, quoting the reference number, that they possess the latest issue. Any person or company using the product without first making further enquiries as to the suitability of the product for the intended use does so at his own risk, and Ronacrete Ltd can accept no responsibility for the performance of the product, or for any loss or damage arising out of such use.