

axis

Automatic Entrance Systems

STANLEY®

ProCare 8300BP

THE SPACE OPTIMIZING ICU DOOR SOLUTION
DELIBERATELY DESIGNED WITH RESPECT FOR PATIENTS
AND CAREGIVERS IN HEALTHCARE ENVIRONMENTS



THE PROCARE DIFFERENCE

The space-optimizing ICU door solution, this compact 4-panel bi-part is the newest alternative to the standard ICU door. With a smaller breakaway arc, you can meet NFPA corridor codes and never have to give up a square inch of your patient room design. Effortless one-handed operation slides both center panels simultaneously. Our exclusive soft open/close prevents loud slamming and extends the life of the door.



Protect the patient

Wide clear door opening* at 1044mm on an 2438mm door and 1196mm on 2743mm. Eliminate dangerous snagging of IV lines and equipment with our catch-free contoured handle and retractable positive latch hook shield.



Promote healing

Easy and more controlled breakaway and return with our new intuitive swing-out button. Quiet and flawless operation with swing out guidance system.

RATINGS*

Smoke & Draft

Leakage rated under ANSI/UL1784 and labeled as a smoke barrier. Learn More

- Smoke and Draft Seals
- Positive Latching With Retractable Positive Latch Hook Shield
- Identifiable Sticker For Rapid Commissioning

Infection Control

Leakage rated, tested to ASTM E283-04 standards and in compliance with the 2014 FGI guidelines for pressurized Airborne Isolation Infection Rooms.

- Concealed Bottom Sweeps
- Perimeter Seals
- Self Closing

* Restrictions may apply such as overall frame height, sliding/breakaway panel width and glazing.

All door packages are custom manufactured to fit your job requirements up to 6mm increments. For sizes greater or smaller than typical, contact Axis.

STANDARD FEATURES

Catch-free Contoured Handle
Swing Out Button
Swing Out Guidance System
Soft Open/Close

OPTIONS

Integral Blinds
Positive Latching With Hook Shield
Self-Closing

WATCH PROCARE 8300BP IN ACTION

<https://youtu.be/tWfi84fXMT8>

TECHNICAL SPECIFICATIONS

CONFIGURATIONS	4-Panel Bi-Part, Smoke & Draft, Trackless, Manual
TYPICAL HEIGHT	2235mm; Taller Available
TYPICAL WIDTH	2438mm, Range 2134mm to 3656mm
HEADER SIZE	101mm Nominal Height
BREAKAWAY TYPE	Breakaway From Full Slide Open Position
JAMB DIMENSION	114mm x 22mm
CLEAR DOOR OPENING WIDTH†	Range: 892mm to 1654mm; 1044mm at 2438mm (Std) Width
SUPPORTED GLAZING	114mm (Std); 22mm, 13mm, 25mm Insulated
STILES	Narrow
BOTTOM RAILS	101mm (Std), 152mm, 203mm, 254mm, 305mm, other custom
FINISHES	Anodized, PVDF Paint, Anti-Microbial (Touch Points or All)
HARDWARE	Catch-free Contoured Handle Option: Positive Latch with Hook Shield, Single-Point Locking, Concealed Self Closing
LISTINGS	UL1784
RATINGS	Leakage (Smoke & Draft), +/- Pressure, ASTM E283-04
Leakage (Smoke & Draft), +/- Pressure, STC	
CODES AND STANDARDS	NFPA 101, NFPA 105, IBC
NFPA 101, NFPA 105, IBC	

† Without Positive Latch

Specifications subject to change. Please contact us to ensure accuracy.



Axis Automatic Entrance Systems Ltd

Unit 6, Queens Park Industrial Estate, Studland Road,
Northampton, NN2 6NA.
Tel: 01604 212500 · Fax 01604 212495
Email: sales@axisautomatic.com
www.axisautomatic.com



* DT3/DP3 **DP1/DP3

Specifications are subject to change without prior notice.
All values measured in specific conditions.

