COMPONENT PARTS FOR TEMPERATURE SENSOR MANUFACTURE


Labfacility is a major supplier of component parts for temperature sensor manufacture to UK and overseas companies. Our vast stocks ensure immediate despatch of a wide range of components; non-stock items can usually be supplied within a few days.

- Terminal heads and blocks
- Closed end protection tubes
- ♦ Pot seals for mineral insulated thermocouples
- Stainless steel flexible armour
- ♦ Springs for cable strain relief
- Coiled leads
- Wall mount housings
- **♦** Thermocouple solder





Certificate No. 4746



Plus Thermocouple connectors and cables, probe installation fittings, thermocouple welding equipment and platinum resistance thermometer sensing resistors described in separate brochures.



COMPONENT PARTS FOR TEMPERATURE SENSOR MANUFACTURE


TERMINAL HEADS









| Model | В | KNE | KNS |
|-----------------------|---|---|---|
| DIN form | B 43729 | _ | - |
| Lid | Retained by 2 screws | Screw type with chain | Screw type with chain |
| Process Entry | ½" BSPP | ½" BSPP | 1⁄8" BSPP |
| Conduit Entry | PG16 Plated brass gland fitted | M20 x 1.5mm Plated brass gland fitted | M16 x 1.5mm Plated brass gland fitted |
| Material/ Finish | Cast aluminium/ silver & enamelled | Cast aluminium/ silver & enamelled | Cast aluminium/ silver & enamelled |
| Max Temp | 100°C | 170°C | 170°C |
| Terminal block | * – | *_ | fitted, 4 way |
| Order Code | HB-006 | HB-013 | HB-014 |
| *Accept any blocks de | scribed on the next page | | |







Accessories for Terminal Heads


M20 cable gland
PG16 to M20 thread converter for B head


Order code HA - 001 Order code HF - 025

COMPONENT PARTS FOR TEMPERATURE SENSOR MANUFACTURE

TERMINAL BLOCKS

Ceramic types:







Ceramic, 4 way, screw terminals Ceramic, 4 way, solder terminals

Ceramic, 6 way, solder terminals HT – 044

Order Code

HT - 040

HT - 041

All DIN B compatible


Moulded Types:

ANSI colour coded blocks in glass filled thermoplastic for 220°C continuous use. All contact materials in thermocouple alloy (type R in copper / copper alloy).

Yellow, 2 way, type K Black, 2 way, type J Blue, 2 way, type T Green, 2 way, type R/S White, 4 way for PRT Order Code HT - 051 HT - 053 HT - 052 HT - 055 HT - 054

IEC 584 colours available to special order Duplex thermocouple blocks available: details on application.

All DIN B compatible




CLOSED END STAINLESS STEEL TUBES


Round Ended (316 stainless steel). Pressure tested to 150psi.

| Outside Dia | Wall thickness | Length | Order Code |
|-------------|----------------|--------|------------|
| 2.1mm | 0.010" | 50mm | SA-100 |
| 3mm | 0.010" | 110mm | SA-101 |
| 3mm | 0.010" | 160mm | SA-102 |
| 4mm | 0.020" | 120mm | SA-105 |
| 6mm | 0.020" | 110mm | SA-108 |
| 6mm | 0.020" | 160mm | SA-109 |
| 6mm | 0.020" | 250mm | SA-110 |
| 1/8" | 0.010" | 110mm | SA-103 |
| 1/8" | 0.010" | 160mm | SA-104 |
| 3/16" | 0.020" | 110mm | SA-106 |
| 3/16" | 0.020" | 200mm | SA-107 |
| 1/4" | 0.020" | 250mm | SA-111 |

"Pencil" pointed tubes (304 stainless steel) for penetration probes.

| . onon points | - tabes (55 : 5tan 115 | oo otool, ioi poi | onanon proboc |
|---------------|------------------------|-------------------|---------------|
| Outside diam. | Wall Thickness | Length | Order Code |
| 3mm | 0.014" | 75mm | SA-201 |
| 3mm | 0.014" | 145mm | SA-202 |
| 4mm | 0.016" | 110mm | SA-203 |
| 4mm | 0.016" | 150mm | SA-204 |
| 4mm | 0.016" | 170mm | SA-205 |
| 4.5mm | 0.016" | 170mm | SA-206 |
| 6mm | 0.016" | 170mm | SA-207 |






POT SEALS FOR MINERAL INSULATED THERMOCOUPLES (304 stainless steel)

| Туре | Dim | ensions |
|-----------------|-------------|----------------|
| Plain, 1mm | (1/4" O/D x | 25mm long) |
| Plain, 1.5mm | (1/4" O/D x | 25mm long) |
| Plain, 3mm | (1/4" O/D x | 25mm long) |
| Plain, 4.5mm | (9.5mm O/ | D x 40mm long) |
| Plain, 6mm | (9.5mm O/ | D x 40mm long) |
| 8mm ISO threa | ded, 1mm | (38mm long) |
| 8mm ISO threa | ded, 1.5mm | (38mm long) |
| 8mm ISO threa | ded, 3mm | (38mm long) |
| 8mm ISO threa | ded, 6mm | (38mm long) |
| 1/8" BSP thread | ded, 1.5mm | (38mm long) |
| 1/8" BSP thread | ded, 3mm | (38mm long) |

| Order Code |) |
|------------|---|
| LW-130 | |
| LW-131 | |
| LW-132 | |
| LW-133 | |
| LW-134 | |
| LW-147 | |
| LW-145 | |
| LW-139 | |
| LW-146 | |
| LW-137 | |
| LW-138 | |



Type Dimensions (38mm long) 1/8" BSP threaded, 4.5mm 1/8" BSP threaded, 6mm (38mm long)

Order Code LW-141 LW-142

'BELL' SPRINGS FOR PROBE CABLE STRAIN RELIEF (HS3 spring steel)

| Probe dia. | Length | Order Code |
|------------|--------|-------------------|
| 4.5mm | 35mm | CA-090 |
| 6.0mm | 35mm | CA-092 |




STAINLESS STEEL ARMOUR (grade 304)

| Bore | Outside dia. | Order Cod |
|-------|--------------|-----------|
| 1/8" | 5.18mm | WC-035 |
| 3/16" | 6.78mm | WC-034 |
| 5mm | 7.00mm | WC-021 |
| | | |



COILED LEADS, PVC INSULATED

| Туре | Extension length | Order Cod |
|---------------|------------------|-----------|
| Type J | 1.5m | WJ-088 |
| Type K | 1.5m | WK-084 |
| Type T | 1.5m | WK-090 |
| 4 core copper | 2m | WC-017 |
| | | |



WALL MOUNTING BOX FOR AIR **TEMPERATURE SENSING**

Type Box only (2 part, moulded). (85 x 85 x 30mm) **PCB** Terminal block for PCB

Order Code PA-004

LW-454

LW-455



SOLDER FOR THERMOCOUPLE WIRE

Alloy 450 Tin/ Lead Silver solder.

Order Code WX - 004



For details of Thermocouple Connectors, Cables, Probe, Installation fittings, Thermocouple Welding Equipment and Platinum Resistance Thermometer Sensing Resistors please refer to separate data sheets available on request.

Specifications, dimensions and availability may be subject to change.