

# G-TURBO 650

Multi-color printer for BIG parts printing




Large touch screen panel



4 Independent pad cylinders



Turbo pad clean feature



Pad in/out stroke for max. throat depth



Stable granite stone machine structure



Precision servo product shuttle (DRE)

## FEATURES

- Turbo pad clean design for multi-color printing
- Revolutionary Granite stone machine structure for performance & stability as well as protect our environment
- Both pad & printing plate platform in / out design for max. product size
- Four independent pad cylinders
- Pneumatic pad in / out carriage
- Servo drive product shuttle attachment
- Four sealed ink cup set up
- Able to use laser engraved Green plate, thin steel plate and polymer plate
- Dead-on printing plate registration for quick job change
- PLC control with large touch screen panel
- Programmable pad cleaning cycle
- Programmable pad stroke and speed adjustment
- Dwell and delay time
- Complete cabinate with light beam curtain (Optional)

## SPECIFICATIONS

|                                |                          |
|--------------------------------|--------------------------|
| Ink cup size :                 | Ø125 & 130 mm x 4        |
| Printing plate size :          | 150 x 350 mm             |
| Max. speed : (dry cycle) *     | 450 / hr.                |
| Pad cylinder :                 | Ø50 x 125 mm x 4         |
| Pad carriage stroke (in/out) : | 250 mm                   |
| Power :                        | 110/220V                 |
| Air consumption :              | 290 litre/min. (approx.) |
| Accuracy +/- :                 | 0.05 mm                  |
| Size : (L x W x H)             | 1,230 x 1,300 x 1,680 mm |
| Weight :                       | 856 kg (approx.)         |

\* Please note that actual output may be affected by print requirement, ink drying condition, load/unload arrangement, pad stroke speed, pad hardness, production setup, product quality and production control.