

IB BETA FENCE

SECURING WHAT MATTERS ACCESS CONTROL SOLUTIONS



Cantilever or sliding rail gates:

Egidia® THE BASE SOLUTION



Range

Self-supporting gates: 4m – 9m width, 1m – 2.4m high



Applications

- Frequent industrial use



Safety

- In compliance with EN13241-1 for use in industrial and commercial environments
- CE-marked
- Equipped with the following safety components as standard:
 - Photocells
 - Safety pressure strips
 - Warning light
- 2 year guarantee on gate, parts and cover



Design

- Universal design
- Standard infill: bar railings
- Optional infill: Nylofor 3D
- Coating:
 - Hot dip galvanised
 - + Polyester (all RAL colours)
- Opening speed 9m/min



Access Control

- Functional option for access control:
 - Remote controls
 - Key switch
 - Key pad
 - Vehicle induction loop



Benefits

- Excellent value for money
- External FAAC gate operator
- Quick and easy installation:
 - Pre-wired and fully assembled

manual – motorizable – fully automated

Robusta® THE STRONG SOLUTION



Range

3m – 12m opening per gate, openings of up to 24m available with double Robusta. Standard height options from 1m – 2.4m



Applications

- Frequent to intensive industrial use



Safety

- In compliance with EN13241-1 for use in industrial and commercial environments
- CE-marked
- Equipped with the following safety components as standard:
 - Photocells
 - Safety pressure strips
 - Warning light
- 10 year guarantee on gate, frame and posts
- 2 year guarantee on automation (detailed terms and conditions available on request)



Design

- A harmonious and robust design
- Standard infill: bar railings
- Optional infill: Nylofor 2D / 2DS / 3D / F and Securifor 358
- High-grade coating: internally and externally galvnrnised, finished with polyester powder coating (available in all RAL colours)
- Opening speed 9m/min



Access Control

- Functional option for access control:
 - Remote controls
 - Key switch
 - Key pad
 - Vehicle induction loop



Benefits

- Robust construction with a broad range of applications
- External FAAC gate operator
- Quick and easy installation:
 - Ground templates available on request
 - Pre-wired and fully assembled
- Motor and controller contained in lockable cabinet

Cantilever automatic gates

Bekamatic® THE EXPERT SOLUTION



Range

3m – 12m opening per gate, openings of 24m available with double Bekamatic. Standard height options 1m – 2.4m (other sizes available on request)



Applications

- High security intensive industrial and commercial use



Safety

- In compliance with EN13241-1 for use in industrial and commercial environments
- CE-marked
- Equipped with the following safety components as standard:
 - Photocells (2 pairs)
 - Safety pressure strips (5 pieces as standard)
 - Key switch
 - Warning light
- Automation and controls secured in lockable cabinet
- 10 year guarantee on gate, frame and posts
- 2 year guarantee on automation (terms and conditions on request)



Design

- Sleek aligned design
- Standard infill: bar railings
- Optional infill:
 - Nylofor 3D / 2D / 2DS / F
 - Securifor 353
 - Lamella privacy screen
- Excellent corrosion resistance due to zinc, epoxy and polyester layers
- Available in all RAL colours
- Resilient automation tested under the most extreme conditions
- Standard opening speed 12m/min



Access Control

- Unlimited options for access control:
 - Remote control, key fob, key switch, keypad, card reader, intercom, videophone, GSM module, vehicle induction loop



Benefits

- Fast opening speed option available 18m/min
- Our most versatile gate with a broad range of options
- Easy installation:
 - Ground templates available on request
 - Pre-wired and fully assembled

Trackless bi-folding high speed gates

Faldivia® THE FAST SOLUTION



Range

Gate opening width 4m – 12m. Standard heights 2m and 2.4m (other sizes available on request)



Applications

- Intensive use when speed and security are paramount



Safety

- In compliance with EN13241-1 for use in industrial and commercial environments
- CE and TUV marked
- Incorporating cutting-edge safety technology
- 2 year guarantee on automation
- 10 year coating guarantee



Design

- Faldivia is available depending on your requirements:
 - Completely hot dip galvanised across the whole construction or Hot dip galvanised posts and aluminium gate wings
- Standard infill: bar railings
- Optional infill: Nylofor 2D / 2DS / F
 - Securifor 358
 - Perforated plate
- Available in all RAL colours



Access Control

- Dual ball bearings ensure hassle-free operation under heavy loads
- Functional option for access control:
 - Key fob, key switch, vehicle induction loop, control buttons



Benefits

- Gate wings retract fully behind posts ensuring minimal risk from vehicle damage
- Permanent or temporary site solutions available
- Sturdy assembly
- High speed site security
- Excellent quality and competitively priced
- Pre-wired and fully assembled

Tried, tested, trusted

ALSO IN OUR RANGE:

From gates to turnstiles and barriers, Betafence offer a range of guaranteed fully installed solutions that put you in control. With various heights, widths, professional expertise and over 135 years of securing what matters, Betafence can help to secure your perimeter access.



SWING GATES



PUBLIFOR®



BOLLARDS



TURNSTILES



BARRIERS

B BETAFENCE

First Floor, Unit B, Forge House, 21 Carbrook Hall Road, Sheffield S9 2EH

T: 0114 256 7800

E: sales.sheffield@betafence.com

W: www.betafence.co.uk