

# FLIP-UP FACE SHIELD

Users will be thrilled by the lightness and design of this flip front protector. The RELRSI version is anti-fog acetate with a thickness of 1.5 mm that will protect you against short circuit electric arcs.



RELRSI



FARELRSI



RELPSI



FARELPSI













200 g

- + POLYPROPYLENE**
- + ADJUSTABLE HEADBAND**
- + PROTECTION AGAINST SHORT CIRCUIT ELECTRIC ARCS (RELRSI VERSION)**
- + 19 CM X 29 CM FL IP-UP FACE SHIELD**

**bolle**  
SAFETY

# FLIP-UP FACE SHIELD

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
<b>PROTECTEUR RELEVABLE</b>	 Acetate lens	RELRSI	2C-1,2  2 B 8 N C€	 EN166 3 8 B C€	Anti-fog (N)
	 Spare acetate lens	FARELRSI	2C-1,2  2 B 8 N C€	-	Anti-fog (N)
	 Polycarbonate	RELPSI	 1 F C€	 EN166 3 8 B C€	Anti-scratch/Anti-fog
	 Spare polycarbonate lens	FARELPSI	 1 F C€	-	Anti-scratch/Anti-fog

## LENS MARKING

### Optical class symbols:

1. Continuous work
2. Intermittent work


### Use symbols:

8. Electrical short circuit arc

### Mechanical strength symbols:

- B.** Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s
- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s

### Others symbols:

- N.** Resistance to fogging (optional)
- C€ European standard  Manufacturer name


## FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

3. Liquid droplets or splashes

8. Electrical short circuit arc

- B.** Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s

C€ European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

## CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

PACKAGING AND EAN 13 CODE				
	RELRSI	FARELRSI	RELPSI	FARELPSI
Individual plastic bag	3660740001957	3660740001520	3660740003487	3660740003494
50 face shields or 250 spare lenses per outer pack	3660740201951	3660740201524	3660740203481	3660740203498

CHARACTERISTICS	
LENSES	Acetate - 1,5 PC - 1,0 mm
FRAME	PP
TEMPLES	Non applicable
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	FARELRSI / FARELPSI



01/10/2013

Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

**bolle-safety.com**

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle**  
SAFETY