

ULTRAVISOR



ULTRAVISOR

Areas of application & use:

- [1] Face protection visor for electricians (arcing faults)
- [2][3][6][7] Face protection visor for mechanical work
- [4][5] Face protection visor for working with chemicals

WELDING PROTECTION



All details of Welding Protection models from p.104

[8]

ULTRAVISOR	341 g	EN 166 3 9 B	Acetate / Polycarbonate	100%	1 pc.	Single-hand twist lock
Features	Weight	Code - housing	Face visor	UV protection	Packing unit	Head strap

<ul style="list-style-type: none"> Smooth-hinged face-protection visor Exceptionally comfortable to wear due to its low weight Face-protection visor for electricians Face-protection visor for welding jobs Exchangeable face visor 	<ul style="list-style-type: none"> Perfect all-round vision with complete coverage of the face Strong, sweat-absorbing towelling head strap Available with a polycarbonate visor Face visor also available with chin support Face visor edged with a rubber protector 	<p>Customized configuration or branding with colour and logo on request</p>
---	--	---

Fig. no.	HOUSING		VISOR PROPERTIES							ULTRAVISOR
	colour(s)		material	thickness	coating(s)*		colour	chin support	code(s)	article no.
[1]	Black		Polycarbonate	1,5 mm			Clear		1 B 8 9 CE	9507 111 EL
[2]	Black		Polycarbonate	1 mm	AF	AS	Clear		1 B N CE	9507 155
[3]	Black		Polycarbonate	1 mm	AF	AS	Clear	yes	1 B N CE	9507 155 C
[4]	Black		Acetate	1 mm	AF	AS	Clear		1 F 9 CE	9507 255
[5]	Black		Acetate	1 mm	AF	AS	Clear	yes	1 F 9 CE	9507 255 C
[6]	Black		Polycarbonate	1 mm			Clear		1 B 9 CE	9507 111
[7]	Black		Polycarbonate	1 mm			Clear	yes	1 B 9 CE	9507 111 C
[8]	Black		Acetate	1 mm	HC		Green		1 F 9 CE	9507 135
[9]	Black		housing, without visor							9507 999

* Coatings: HC = scratch-resistant | AF AS = anti-fog, antistatic, scratch-resistant | HC AF AS = scratch-resistant, anti-fog, antistatic